

Model M71-H-6



The Manchester model M71-H-6 is a hydraulically operated machine that uses a programmable six position rotary tool holder. The machine is easily programmed to make one through six strokes. The rotary tool holder allows for the use of larger spring loaded punches required for many of today's end form requirements. Some of the many features and options available for this machine are listed on the other side.



www.manchestertoolanddie.com

# Manchester Model M71-H-6 Tube End Forming System

## MTD SPECIFICATIONS

# Standard Equipment

Cycle Time: 2.2 to 9 seconds\*Tube O.D. Capacity: 1.5"

• Maximum Jaw Opening: 1.75"

• Ram Cylinder: 3-1/4" bore x 6" stroke

• Ram Force: 15 tons (maximum)

• Clamp Cylinder: 2-1/2" bore x 2-1/2" stroke

• Clamp Force: 17-1/2 tons (maximum)

Hydraulic Unit: 15HP 22 GPM
Working Pressure: 1200 PSI
Maximum Pressure: 2500 PSI

Air Required: 40 to 80 PSI & 3 CFMElectrical Required: Customer Spec.


• 12 Month Warranty on Machines

\* Cycle time depends on the application and optional equipment.

# Valuable Options

- Larger Hydraulic Unit Larger Ram Cylinders
- Autoload & Unload Systems
- Custom Cycle Start Initiators
- · Part Present Sensor
- · Panelview Touch Screen
- Light Curtains
- Custom Painting

#### CALL FOR AVAILABLE STOCK MACHINES



Machine weight without oil is approximately 5,500 lbs.

#### Advanced Features

- 1 to 6 Stroke and Double Index Capability
- Easy Access for Tooling Changeovers and Service
- Compact Footprint



Manchester Tool & Die, Inc. also works with the customer to create machines for unique applications.

## Manchester Tool & Die, Inc.

P.O. Box 326 • 601 South Wabash Road • North Manchester, IN 46962

Phone: 260-982-8524 • Fax: 260-982-4575 Email: sales@manchestertoolanddie.com

Exceeding Expectations Since 1960 • www.manchestertoolanddie.com