16645 Heimbach Road
Three Rivers, MI 49093
Phone: 269-279-5123
Fax: 269-279-6337
www.wfwells.com

J2008

W. F. WELLS MODEL **B-25-3A3 CNC**

Specifications

Capacity ..... 25” High x 40” Wide, 25.5” Round
Weight Capacity ..... 14,000 lbs
Blade Speed ..... 60-500 SFPM
Blade Size ..... 2" X .063" X 26'-6", 2⅝ optional
Blade Guide ..... Spring Tensioned Carbide Blocks with Idle Roller Back-up
Blade Tension ..... Hydraulic
Bandwheel Size ..... 26”
Vise ..... Hydraulic
Blade Drive ..... 15 HP, AC Vector Drive
Sawing Force ..... 0-1,000 lbs
Coolant Capacity ..... 15 Gallons
Hydraulic Capacity ..... 20 Gallons
Hydraulic Drive ..... 5 HP Motor
Work Height ..... 35"
Outfeed Table ..... 12" X 41"
Vise Jaw Height ..... 17"
Barfeed Projection ..... 0 - 36" CNC Controlled
Projection Accuracy ..... +/- .002"
Shuttle Indexes ..... Unlimited
Remnant End ..... 14"
Shipping Weight ..... 11,400 lbs
Electrics ..... Wired to NFPA 79 Machine Tool Standards
Hydraulic Positioned Guide Arm, Powered Blade Brush, Blade Break/Stall Switch
CNC Programmable Controlled with Color Touch Screen
500+ Job Selection
Automatic Kerf Compensation

Voltage	Order Number
208-60-3	0010740
230-60-3	0010741
460-60-3	0010742
575-60-3	0010743

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description	Order Number
Discharge Worktable 40” Wide x 56” Long	0056061
Optional Barfeed AF-12 40” Wide x 144” Stroke	0050089
Hydraulic Chip Conveyor	0056069
Holddown, Saw Vise	0056064
Hydraulic Holddown, Barfeed Vise	0050107
Outboard Vise with Hydraulic Holddown	0056063
Outboard Vise	0056062
Non-Powered Conveyor 36” x 5’	0056198
Non-Powered Conveyor 36” x 10’	0056199
40” Conveyor	Consult Factory for Pricing
High Speed Drive & Guides (1½” Blade) 500-3000 SFPM	

Consult Factory for Additional Accessories

MADE IN USA