



Model B-25-4

Semi-Automatic
Twin-Post Bandsaw



MADE IN THE USA



MACHINE SPECIFICATIONS

Capacity @ 90°	25" High X 40" Wide, 25½" Diameter
Capacity @ 45°	25" High X 24" Wide
Weight Capacity	15,000 lbs
Blade Speed	60-500 SFPM
Blade Size	2⅝" X .063" X 26'-6"
Blade Guide	Spring Tensioned Carbide Blocks w/ Idle Roller Backup
Blade Tension	Hydraulic
Bandwheel Size	26"
Vise	Hydraulic
Blade Drive	15 HP, AC Vector Drive
Sawing Force	0-1000 lbs
Coolant Capacity	20 Gallons
Hydraulic Capacity	20 Gallons
Hydraulic Drive	5 HP Motor
Work Height	28"
Outfeed Table	24" x 40"
Vise Jaw Height	17"
Shipping Weight	8,200 lbs
Electrics	Wired to NFPA 79 Machine Tool Standards
Ship Dimensions	156" x 55" x 98"

* Specifications subject to change without notice

STANDARD EQUIPMENT

2⅝" Bi-Metal Blade
AC Vector Drive
Spring Loaded Carbide Guides
Hydraulic Vise Operation
Blade Tension Indicator
Hydraulic Auger Style Chip Conveyor
Built-In Coolant System
45° Swiveling Vise
Hydraulic Powered Blade Brush
TEFC Motors
Fused Disconnect with Lock-Out
Console Controlled Blade Speed
Feed Pressure Monitor/Regulator
Low Voltage/Overload Protection
Electronic Door Safety Interlocks
Work Lights
Hydraulic Positioned Guide Arm
All Safety Guards
Operator Manual and Parts List
LED Positive Feed Readout
Semi-Automatic Operation
Blade Break/Stall Switch

W.F. Wells, Inc.

16645 Heimbach Road • Three Rivers, MI 49093

Phone: (269) 279-5123 • Fax: (269) 279-6337

Web page: www.wfwells.com • E-mail: info@wfwells.com