

Model F-1630-2 **Horizontal Band Cut-Off Machine**





The F-1630-2 series features automatic preset hydraulic blade tension, a hydraulic vise with variable clamping pressure and increased sawing pressure for severe applications. These features ensure easier and more productive operator control.

MACHINE SPECIFICATIONS

Capacity @ 90° Rectangular 16" H x 30" W, Round 16" Capacity @ 45° Rectangular 16" H x 13" W, Round 13"

Weight Capacity 5,000 lbs Blade Speed 60-500 SFPM Blade Size 1¼" x .042" x 16'8"

Blade Tension Hydraulic Bandwheel Size 20"

Vise Hydraulic, Full Stroke

Sawing Force 0-750 lbs

71/2 HP, AC Vector Drive **Blade Drive**

Hydraulic Drive 2 HP Motor

Work Height 26"

Coolant Capacity 15 Gallons Hydraulic Capacity 20 Gallons Shipping Weight 2,500 lbs

Machine Dimensions 52" L x 118" W x 86" H

*Specifications Subject to Change Without Notice

STANDARD EQUIPMENT

11/4" Bimetal Blade

Carbide Guides with Backup Rollers Hydraulic Vise with Variable Pressure

Hydraulic Blade Tension Semi-Automatic Operation

45° Swiveling Vise

Blade Powered Rotary Cleaning Brush

TEFC Motors

Fused Disconnect with Lockout

NFPA-79 Electrics

Automatic End-of-Cut Shut Off

Quick and Easy Blade Speed Change Blade Speed and Work Selector Chart

Feed Pressure Monitor/Regulator

All Safety Guards

Operator Manual and Parts List

Factory Trained Start-Up

W.F. Wells, Inc.

16645 Heimbach Road • Three Rivers, MI 49093 Phone: (269) 279-5123 - Fax: (269) 279-6337 Web page: www.wfwells.com · E-mail: info@wfwells.com