

IRB 6640 / IRB 6640ID Industrial Robot

Main Applications

Material handling
Machine tending
Spot welding

IRB 6640 – a strong robot for numerous applications

The IRB 6640 / IRB 6640ID is available in different arm lengths and matching handling capacities. It is based on proven components from earlier generations, to ensure ease of maintenance and exchangeability as well as high up time.

Upper arm extenders and different wrist modules allow customization to each process. As the robot can bend fully backwards, the working range is greatly extended allowing it to fit well into dense production lines. Typical application areas are material handling, machine tending and spot welding.

The robot is also available with different options such as Foundry Plus 2, Foundry Prime 2 and Clean Room for different working environments.

IRB 6640ID with Internal Dressing (ID) has its process cables routed inside the upper arm. The cables follow the robot arm's every motion instead of swinging in irregular patterns.

Higher payload

The maximum payload is 235 kg, which makes it suitable for a variety of heavy material handling applications. The robot also follows the tradition of having outstanding inertia capabilities, which makes it possible to handle heavy and wide parts. ABB robots are also known for their collision resistance.

The IRB 6640ID's 200 kg payload capacity meets the requirements from the heaviest spot welding applications.

Easy maintenance

Simplified fork lift pockets and more space in the robot foot make the robot easier to maintain.



Increased path performance

The IRB 6640 is compatible with second generation TrueMove™ and QuickMove™. The software allows for more accurate motion in shorter programming times for improved processes. The software also monitors internal robot loads which reduces the risk of overload and increases the robot's life cycle.

Passive safety features

Passive safety features include load identification, movable mechanical stops, Electronic Positions Switches (EPS) and a stiff steel structure.

IRB 6640ID – Internal Dressing in the upper arm

The IRB 6640 with Lean ID has its process cabling for spot welding routed inside the upper arm. This provides more motion control as well as other benefits, like predictable dress pack lifetime, longer dress pack lifetime and less spare part cost; a more compact robot when dressed and also a reliable simulation of dress pack motion.

IRB 6640 / IRB 6640ID

Specification

Robot versions	Reach	Handling capacity	Center of gravity	Wrist torque
IRB				
6640-180*	2.55 m	180 kg	300 mm	961 Nm
6640-235*	2.55 m	235 kg	300 mm	1324 Nm
6640-205*	2.75 m	205 kg	300 mm	1264 Nm
6640-185*	2.8 m	185 kg	300 mm	1206 Nm
6640-130	3.2 m	130 kg	300 mm	1037 Nm
6640ID-200	2.55 m	200 kg	300 mm	1262 Nm
6640ID-170	2.75 m	170 kg	300 mm	1190 Nm

*Available as Lean ID option.

Extra loads can be mounted on all variants.

50 kg on upper arm (except ID) and 250 kg on frame of axis 1.

Number of axes: 6

Protection Complete robot IP 67

Mounting: Floor mounted

IRC5 Controller variants: Single cabinet, Dual cabinet

Performance

Positions repeatability 0.07 mm

Path repeatability 0.7 mm

Axis movements	Working range 6640	Working range 6640ID	Axis max speed 6640
Axis 1 Rotation	+170° to - 170°	+170° to - 170°	100 - 110°/s
Axis 2 Arm	+85° to - 65°	+85° to - 65°	90°/s
Axis 3 Arm	+70° to - 180°	+70° to - 180°	90°/s
Axis 4 Wrist	+300° to - 300°	+300° to - 300° *	170 - 190°/s
Axis 5 Bend	+120° to - 120°	+100° to - 100°	120 - 140°/s
Axis 6 Turn	+360° to - 360°	+300° to - 300°	190 - 235°/s

* For IRB 6640ID axis 4 and 6 together max +300° to -300°

A supervision function prevents overheating in applications with intensive and frequent movements.

Electrical Connections

Supply voltage 200-600 V, 50/60 Hz

Power consumption ISO-Cube 2.7kW

Physical

Dimensions robot base 1107 x 720 mm

Weight 1310 - 1405 kg

Environment

Ambient temperature for mechanical unit

During operation + 5° C (41°F) - +50°C (122°F) *

During transportation and storage for short periods - 25° C (13°F) - +55°C (131°F)

up to +70° C (158°F)
(max 24h)

Relative humidity Max 95 %

Noise level Max 71 dB (A)

Safety Double circuits with supervision, emergency stops and safety functions, 3-position enable device

Emission EMC/EMI-shielded

Options Foundry Plus 2

Foundry Prime 2

Clean Room, class 5 - IRB 6640-180
(certified By IPA)



* In a high-speed press tending application, max ambient temperature is 40 °C.

Data and dimensions may be changed without notice.

Working range


IRB 6640-180/2.55 (IPA certified),

IRB 6640-235/2.55,


IRB 6640ID-200/2.55

IRB 6640-205/2.75,

IRB 6640ID-170/2.75




* 1549 for 6640ID



* 1682 for 6640ID

IRB 6640-185/2.8



IRB 6640-130/3.2

