



FG SERIES FIBERGLASS COOLING TOWERS

FG Series cooling towers offer unparalleled corrosion resistance, energy efficiency and performance.

If your cooling temperature requirements range from 85°F upward, you may reduce your process water consumption up to 98.5% by using cooling towers to remove process heat. AEC Cooling Tower Systems are used wherever a reduction of water costs and/or control of mineral precipitation associated with cooling applications is desired.



FG Series Tower

STANDARD FEATURES

- High-efficiency induced-draft design
- Balancing valve and pressure gauge
- Lightweight non-corrosive fiberglass shell with fiberglass side seams
- Vertical air discharge
- Stainless steel hardware
- Factory-tuned fan blade pitch
- Totally-enclosed non-ventilated energy-efficient TENV fan motor
- Large inspection/access door
- Anti-clog ABS nozzle(s)
- Bottom outlet (requires a 24" [61 cm] minimum support base under the tower)
- PVC Fill and Drift eliminators with ultraviolet (UV) protection
- Exterior gel coat/UV inhibitor
- 2 year warranty on parts
- 1 year warranty on fan motors
- 1 year warranty on labor (labor in North America)

OPTIONAL FEATURES

- 460/3/60 or 230/3/60 starter package, including starter, on/off switch, thermostat, and well (consult factory for 208V or 575V)
- Basin reservoir, to be used where the basin of the tower serves as a reservoir. It is not necessary to purchase this package where an inside reservoir is used. The parts consist of a 0.75" automatic float valve, water outlet basket strainer, and overflow connection (Not recommended for bottom outlet towers).
- Heater, used with basin reservoir option to guard against freeze-up when system is shut down. Includes heater and low water heater shut off.
- Factory startup, including checking motors, flow, adjusting nozzles. Towers must be installed and connected, including all piping and electrical hookups before AEC arrives on site.
- Access ladder, meets OSHA requirements (shipped loose for field installation)
- Side outlet configuration available at no charge

FG SERIES FIBERGLASS COOLING TOWERS

HEAT AND COOL

SPECIFICATIONS

Model	Capacity, ¹ tons (Kcal/hr)	Fan motor, hp (kW)	Amp draw, 460/3/60	Water inlet dia., in. (mm)	Water outlet dia., in. (mm)	Length, in. (cm)	Width, in. (cm)	Height, in. (cm)	Ship. weight, lbs. (kg)	Operating weight, lbs. (kg)
FG 2003	50 (151,200)	2 (1.5)	3.4	4 (102)	4 (102)	64 (163)	64 (163)	104 (264)	600 (273)	1300 (591)
FG 2004	75 (226,800)	5 (3.7)	7.6	4 (102)	6 (152)	64 (163)	64 (163)	125 (318)	750 (341)	1700 (772)
FG 2005	100 (302,400)	5 (3.7)	7.6	4 (102)	8 (203)	82 (208)	82 (208)	121 (307)	1400 (636)	2900 (1317)
FG 2007	125 (378,000)	5 (3.7)	7.6	4 (102)	8 (203)	82 (208)	82 (208)	121 (307)	1500 (681)	3200 (1453)
FG 2009	150 (453,600)	10 (7.5)	14	4 (102)	8 (203)	100 (254)	100 (254)	123 (313)	1950 (886)	3800 (1726)
FG 2011	175 (529,200)	10 (7.5)	14	4 (102)	8 (203)	100 (254)	100 (254)	123 (313)	2100 (954)	4400 (1998)
FG 2015	200 (604,800)	15 (11.2)	21	4 (102)	8 (203)	100 (254)	100 (254)	124 (315)	2600 (1181)	5200 (2361)

¹ Capacity based upon 15,000 BTU/hr (3,024 Kcal/hr) heat rejection per ton (3,024 Kcal/hr chilled water, 3,780 Kcal/hr tower water). Flow equals 3 gpm per ton (1.563 lpm per 1,000 Kcal/hr). Entering water temperature 95°F (35°C), leaving water temperature 85°F (29°C), 78°F (26°C) ambient wet bulb. Consult factory for other requirements.

