AK SERIES UNDER-THE-PRESS AUGER-FEED GRANULATORS

GRANULATE



AK SERIES UNDER-THE-PRESS AUGER-FEED GRANULATORS

The AK Series under-the-press granulators feature built-in simplicity at a low cost and are ideal for size reduction of runners, sprues, blow-molded scrap, small thin wall parts and pre-cut thermoformed web.



AK Series Granulator

STANDARD FEATURES

- Slant cut shearing design
- · Heavy-duty steel welded construction
- · One-piece reverse-flight auger
- · Heavy-duty auger chain drive
- NEMA 12 magnetic across-the-line starter control
- · Casters: two swivel, two fixed
- Reversible screens
- 208, 230, 460 or 575 voltage
- · Meets OSHA safety requirements
- Drum reverser control
- · Lockable, fused disconnect
- Hinged cutting chamber cover

OPTIONAL FEATURES

- · Leg extensions
- · Oversize collection bin
- · Bin level monitor
- · Scissor cut knife arrangement
- Wear/abrasion resistance
- · Reduced auger speed
- · Increased or decreased auger length
- · Standard or custom engineered auger infeed chutes

AK SERIES UNDER-THE-PRESS AUGER-FEED GRANULATORS

GRANULATE

SPECIFICATIONS

Model	НР	Blades: rotor/bed	Rotor Cutting Circle, in. (mm)	RPM	Cutting Chamber Opening, in. (cm)	Auger			Avg.	_	Open	Approx. Dim., in. (cm)			Ship.
						Outer Dia., in. (mm)	Core Dia., in. (mm)	rpm	lbs./hr	Trough Height, in. (cm)	Screen Area, sq. in. (cm ²)	Н	W	L	Weight, lbs. (kg)
AK-68	3	3/2	6 (152)	650	6 x 8 (15 x 20)	6 (152)	2 3/8 (60.3)	70	175 (79)	18 (46)	18.02 (46)	49 (125)	28 (72)	55 (140)	650
	5														(296)
AK-812	5	3/2	8 (203)	620	8 x 12 (20 x 30)	9 (229)	2 7/8 (73.0)	70	250 (113)	25 1/4 (65)	25 1/4 (65)	57 (145)	35 (89)	82 (209)	591 (1300)
	7.5														
AK-1216	10	3/2	12 (305)	560	12 x 16 (30 x 40)	12 (305)	3 7/8 (98.4)	70	450 (204)	32 1/2 (83)	32 1/2 (83)	69 (176)	48 (122)	88 (224)	2400 (1090)
	15														

¹ Throughput based on 3/8" (9.525 mm) screen. Different forms and types of material may change rates.

DIMENSIONS

Model	Α	В	С	D	E
AK-68	55"	49.25"	18"	28"	20.75"
AK-812	81.5"	57"	25.25"	34.5"	43.5"
AK-1216	87.5"	68.5"	32.25"	48"	44"



