

SERIES 35 Scissors Lifts



VERSATILE LIFT TABLES, TURNTABLES & TILTERS

Series 35 is the most versatile and popular family of lifts. This family of lifts can be used in a wide variety of applications – such as pallet build-up and tear-down, part assembly and disassembly and conveyor systems –

to improve worker ergonomics or enhance plant efficiencies. The Series 35 reduces worker fatigue and reduces the risk of back injuries. Series 35 offers a high quality, low cost lifting solution.

S35 SCISSORS LIFTS

KEY FEATURES

- Lubricated-for-life composite bearings on all pivot points
- Solid steel legs with stiffener bars
- Turned, ground, polished and hard-chromed axle pins
- Double-wire braided hydraulic hoses
- Velocity fuses on cylinders
- Polyethylene reservoir
- Maintenance (safety) locks in base frame
- Factory tested to 110% of capacity
- Internally mounted power unit
- Pre-wired power unit with UL approved and labeled control components
- Built and designed in accordance with ANSI MH29.1

OPTIONS

- Pit mounting (requires 8 1/2" lowered height)
- Accordion Skirts
- Portability package



BENEFITS

- Maintenance free bearings, no greasing
- Minimal platform deflection
- Extended bearing life
- Extended hose life for added safety
- Controlled descent in case of severed hose – Safety first!
- Reservoir will not contain rust, weld slag or condensation common with metal tanks. Allows visual checking of oil level.
- Easy access to hydraulic/electrical components for servicing
- Ready to operate lift with zero plumbing and minimal wiring
- Backed by the best warranty in the industry

STANDARD POWER SUPPLY Series 35 all Standard, Extra Wide, Double Long, Double High, and Double Wide models

– The electric motor is internally mounted. It is available in either 1 1/2 hp three-phase or 3/4 hp single-phase, with 24 VAC control voltage unless noted. Some noted models require a remote 5 hp three-phase, with 24 VAC control voltage.

Series 35 Extra Narrow models – The electric motor is externally mounted. It is available in either 1 1/2 hp three-phase or 3/4 hp single-phase, with 24 VAC control voltage.

Series 35 36S15 – The electric motor is internally mounted. It is available in 1/2 hp single-phase with 115 VAC control voltage.

SPECIFICATIONS: 1,500 to 15,000 lb. Capacities, Travel Up to 60"

Travel (in.)	Lifting Capacity (lbs.)	Model No.	Lowered Height (in.)	Raised Height (in.)	Max. End Load (lbs.)	Max. Side Load (lbs.)	Standard Platform & Base Frame (inches)	Maximum Allowable Platform Size (in.)	Raising or Lowering Time (sec.)	Electric Motor (hp)	No. of Cyl.	Shipping Weight (lbs.)
to 24"	2,500	24S25	6 1/2	30 1/2	2,500	2,500	24x36	48x60	8	1.5	1	500
	4,000	24S40	6 1/2	30 1/2	4,000	4,000	24x36	48x60	11	1.5	1	510
	6,000	24S60	6 1/2	30 1/2	4,500	4,500	24x36	48x60	16	1.5	2	530
	8,000	24S80	7	31	4,500	4,500	24x36	48x60	22	1.5	2	650
to 36"	1,500	36S15	6 1/2	42 1/2	1,000	750	24x48	48x72	28	0.5	1	450
	2,500	36S25	6 1/2	42 1/2	2,500	2,500	24x48	48x72	12	1.5	1	610
	4,000	36S40	6 1/2	42 1/2	3,500	3,500	24x48	48x72	17	1.5	1	620
	6,000	36S60	6 1/2	42 1/2	3,500	3,500	24x48	48x72	25	1.5	2	650
	8,000	36S80	7	43	3,500	3,500	24x48	48x72	34	1.5	2	750
to 48"	2,500	48S25	7	55	2,500	2,500	24x64	48x96	16	1.5	1	820
	4,000	48S40	7	55	3,500	3,500	24x64	48x96	22	1.5	1	830
	6,000	48S60	7	55	3,500	3,500	24x64	48x96	33	1.5	2	860
	8,000	48S80	7 1/2	55 1/2	3,500	3,500	24x64	48x96	44	1.5	2	960
to 60"	2,500	60S25	8	68	2,500	2,500	32x87	60x120	22	1.5	1	1,100
	4,000	60S40	8	68	3,500	3,500	32x87	60x120	44	1.5	1	1,150
	6,000	60S60	8	68	3,500	3,500	32x87	60x120	44	1.5	1	1,250
	8,000	60S80	12	72	8,000	8,000	32x90	60x120	36	1.5	2	4,400
	10,000	60S100	12	72	10,000	9,000	32x90	60x120	36	1.5	2	4,500
to 58"	12,000	58S120	12 1/2	70 1/2	12,000	10,000	32x90	60x120	60	1.5	2	4,600
	15,000	58S150	12 1/2	70 1/2	14,000	12,000	32x90	60x120	60	1.5	2	4,700

S35 ROVER - MOBILE SCISSORS LIFT

The versatile Series 35 is even more versatile when it becomes mobile. Now high capacity lifting can easily be moved to and shared among various workstations as required. Simply unlock the wheels and roll to any position required. 110 VAC battery charger included.



SPECIFICATIONS: Series 35 Rover - Portable 12 VDC Scissors Lift Model

Travel (in.)	Lifting Capacity (lbs.)	Model No.	Lowered Height (in.)	Raised Height (in.)	Max. End Load (lbs.)	Max. Side Load (lbs.)	Standard Platform & Base Frame (inches)	Maximum Allowable Platform Size (in.)	Raising or Lowering Time (sec.)	Electric Motor (hp)	No. of Cyl.	Shipping Weight (lbs.)
36"	2,500	36SRV25	14	50	2,500	1,500	24x48	48x72	12*	Battery Operated	1	1,100
	4,000	36SRV40	14	50	3,000	2,500	24x48	48x72	17*		1	1,050
	6,000	36SRV60	14	50	3,000	2,500	24x48	48x72	25*		2	1,100
48"	2,500	48SRV25	14 1/2	62	2,500	1,500	24x64	48x96	16*		1	1,210
	4,000	48SRV40	14 1/2	62	3,000	2,500	24x64	48x96	22*		1	1,260
	6,000	48SRV60	14 1/2	62	3,000	2,500	24x64	48x96	33*		2	1,350

*Varies depending on amp draw in battery.

S35 EXTRA WIDE, EXTRA NARROW

SPECIFICATIONS: Series 35 Extra Wide Platform Scissors Lift Model Specifications: Up to 84" x 120"

Travel (in.)	Lifting Capacity (lbs.)	Model No.	Lowered Height (in.)	Raised Height (in.)	Max. End Load (lbs.)	Max. Side Load (lbs.)	Standard Platform & Base Frame (inches)	Maximum Allowable Platform Size (in.)	Raising or Lowering Time (sec.)	Electric Motor (hp)	No. of Cyl.	Shipping Weight (lbs.)
to 24"	2,500	24S25EXW	6 1/2	30 1/2	2,500	2,500	48x36	72x60	16	1.5	2	715
	4,000	24S40EXW	6 1/2	30 1/2	4,000	4,000	48x36	72x60	16	1.5	2	715
	6,000	24S60EXW	6 1/2	30 1/2	4,500	4,500	48x36	72x60	16	1.5	2	715
	8,000	24S80EXW	7	31	4,500	4,500	48x36	72x60	22	1.5	2	825
to 36"	2,500	36S25EXW	6 1/2	42 1/2	2,500	2,500	48x48	72x72	25	1.5	2	855
	4,000	36S40EXW	6 1/2	42 1/2	3,500	3,500	48x48	72x72	25	1.5	2	855
	6,000	36S60EXW	6 1/2	42 1/2	3,500	3,500	48x48	72x72	25	1.5	2	855
	8,000	36S80EXW	7	43	3,500	3,500	48x48	72x72	34	1.5	2	965
to 48"	2,500	48S25EXW	7	55	2,500	2,500	48x64	72x96	33	1.5	2	1,095
	4,000	48S40EXW	7	55	3,500	3,500	48x64	72x96	33	1.5	2	1,095
	6,000	48S60EXW	7	55	3,500	3,500	48x64	72x96	33	1.5	2	1,095
	8,000	48S80EXW	7 1/2	55 1/2	3,300	3,500	48x64	72x96	44	1.5	2	1,210
to 60"	2,500	60S25EXW	8	68	2,500	2,500	58x87	84x120	44	1.5	2	2,300
	4,000	60S40EXW	8	68	3,500	3,500	58x87	84x120	44	1.5	2	2,350
	6,000	60S60EXW	8	68	4,500	3,500	58x87	84x120	44	1.5	2	2,400
	8,000	60S80EXW	12	72	6,000	6,000	61x90	90x120	36	5	2	5,200
	10,000	60S100EXW	12	72	10,000	9,000	61x90	90x120	36	5	2	5,300
to 58"	12,000	58S12DEXW	12 1/2	70 1/2	12,000	10,000	61x90	90x120	60	5	2	5,400
	15,000	58S12DEXW	12 1/2	70 1/2	14,000	12,000	61x90	90x120	60	5	2	5,500

SPECIFICATIONS: Series 35 Extra Narrow Platform Scissors Lift Model Specifications: Remote P.U.

Travel (in.)	Lifting Capacity (lbs.)	Model No.	Lowered Height (in.)	Raised Height (in.)	Max. End Load (lbs.)	Max. Side Load (lbs.)	Standard Platform & Base Frame (inches)	Maximum Allowable Platform Size (in.)	Raising or Lowering Time (sec.)	Electric Motor (hp)	No. of Cyl.	Shipping Weight (lbs.)
to 24"	2,500	24S25EXN	6.5	30 1/2	2,500	2,500	16x36	32x60	8	1.5	1	450
	4,000	24S40EXN	6.5	30 1/2	4,000	4,000	16x36	32x60	11	1.5	1	450
to 36"	2,500	36S25EXN	6.5	42 1/2	2,500	2,500	16x48	32x72	12	1.5	1	560
	4,000	36S40EXN	6.5	42 1/2	3,500	3,500	16x48	32x72	17	1.5	1	570
to 48"	2,500	48S25EXN	7	55	2,500	2,500	16x64	32x96	16	1.5	1	770
	4,000	48S40EXN	7	55	3,500	3,500	16x64	32x96	22	1.5	1	780
to 60"	2,500	60S25EXN	8	68	2,500	2,500	24x87	40x120	22	1.5	1	1,600
	4,000	60S40EXN	8	68	3,500	3,500	24x87	40x120	44	1.5	2	1,650
	6,000	60S60EXN	8	68	4,500	3,500	24x87	40x120	44	1.5	2	1,700

S35 DOUBLE LONG, DOUBLE HIGH

The Series 35 family of lifts can accommodate application that require either a small footprint with high travel with Double High lifts, or oversized platforms with Double Long or Double Wide models. These affordable lifts combine standard Series components to ensure durability and dependable performance.



Travel (in.)	Lifting Capacity (lbs.)	Model No.	Lowered Height (in.)	Raised Height (in.)	Max. End Load (lbs.)	Max. Side Load (lbs.)	Standard Platform & Base Frame (inches)	Maximum Allowable Platform Size (in.)	Raising or Lowering Time (sec.)	Electric Motor (hp)	No. of Cyl.	Shipping Weight (lbs.)
--------------	-------------------------	-----------	----------------------	---------------------	----------------------	-----------------------	---	---------------------------------------	---------------------------------	---------------------	-------------	------------------------

SPECIFICATIONS: Series 35 Double Long Scissors Lift Model Specifications: Up to 48" x 162"

to 24"	4,000	24S25DL	6 1/2	30 1/2	2,500	4,000	24x74	48x98	16	1 1/2	2	1,100
	6,400	24S40DL	6 1/2	30 1/2	4,000	6,400	24x74	48x98	22	1 1/2	2	1,150
	9,600	24S60DL	6 1/2	30 1/2	4,500	7,200	24x74	48x98	32	1 1/2	4	1,200
	12,000	24S80DL	7 1/4	31 1/4	4,500	7,200	24x74	48x98	44	1 1/2	4	1,400
to 36"	4,000	36S25DL	6 1/2	42 1/2	2,500	4,000	24x98	48x122	24	1 1/2	2	1,300
	6,400	36S40DL	6 1/2	42 1/2	3,500	5,600	24x98	48x122	34	1 1/2	2	1,350
	9,600	36S60DL	6 1/2	42 1/2	3,500	5,600	24x98	48x122	25*	5	4	1,400
	12,000	36S80DL	7 1/4	43 1/4	3,500	5,600	24x98	48x122	35*	5	4	1,650
to 48"	4,000	48S25DL	7	55	2,500	4,000	24x130	48x162	32	1 1/2	2	1,700
	6,400	48S40DL	7	55	3,500	5,600	24x130	48x162	22*	5	2	1,750
	9,600	48S60DL	7	55	3,500	5,600	24x162	48x162	33*	5	4	1,800
	12,000	48S80DL	7 3/4	55 3/4	3,500	5,600	24x130	48x162	45*	5	4	2,100
to 60"	4,000	60S25DL	8	68	2,500	4,000	32x176	60x206	22	5	2	2,400
	6,400	60S40DL	8	68	4,000	5,600	32x176	60x206	44	5	4	2,500
	9,600	60S60DL	8	68	4,500	5,600	32x176	60x206	44	5	4	2,600

Std Power unit is a remote 5hp super torque

to 60"	12,000	60S80DL	12	72	8,000	12,000	32x182	60x212	46	5	4	8,800
	16,000	60S100DL	12	72	10,000	14,000	32x182	60x212	46	5	4	9,000
to 58"	20,000	58S120DL	12 1/2	70 1/2	12,000	16,000	32x182	60x212	72	5	4	9,200
	24,000	58S150DL	12 1/2	70 1/2	14,000	20,000	32x182	60x212	72	5	4	9,400

SPECIFICATIONS: Series 35 Double High Scissors Lift Model Specifications: Up to 96" Travel

to 48"	2,400	24S25DH	13	61	2,000	1,000	24x36	36x60	16	1 1/2	2	1,100
	3,400	24S40DH	13	61	3,400	1,600	24x36	36x60	22	1 1/2	2	1,150
	5,400	24S60DH	13	61	3,500	1,600	24x36	36x60	32	1 1/2	4	1,200
	7,000	24S80DH	14	62	3,500	1,800	24x36	36x60	44	1 1/2	4	1,275
to 72"***	1,900	36S25DH	13	85	1,900	1,000	24x48	36x72	24	1 1/2	2	1,300
	3,400	36S40DH	13	85	3,000	1,400	24x48	36x72	34	1 1/2	2	1,350
	5,400	36S60DH	13	85	3,000	1,400	24x48	36x72	25*	5	4	1,400
	5,400	36S80DH	14	86	3,000	1,400	24x48	36x72	35*	5	4	1,475
to 96"***	7,000	48S25DH	14	110	1,700	1,000	24x64	36x96	32	1 1/2	2	1,700
	1,700	48S40DH	14	110	2,500	1,400	24x64	36x96	22*	5	2	1,750
	3,200	48S60DH	14	110	3,000	1,400	24x64	36x96	33*	5	4	1,800
	5,200	48S80DH	15	111	3,000	1,400	24x64	36x96	45*	5	4	1,875

*Note: Remote 5 hp super torque power units are standard for extra oil volume. ***72" and 96" travel models may require guide systems and gates and enclosures. Consult with the factory.

S35 DOUBLE WIDE, EXTRA WIDE DOUBLE LONG



Velocity fuses
to prevent
uncontrolled
descent

Maintenance
locks for safe
repair
environment

Travel (in.)	Lifting Capacity (lbs.)	Model No.	Lowered Height (in.)	Raised Height (in.)	Max. End Load (lbs.)	Max. Side Load (lbs.)	Standard Platform & Base Frame (inches)	Maximum Allowable Platform Size (in.)	Raising or Lowering Time (sec.)	Electric Motor (hp)	No. of Cyl.	Shipping Weight (lbs.)
-----------------	-------------------------------	--------------	----------------------------	---------------------------	-------------------------------	--------------------------------	--	--	--	---------------------------	----------------	------------------------------

SPECIFICATIONS: Series 35 Double Wide Scissors Lift Model Specifications: Up to 72" x 96"

to 24"	4,000	24S25DW	6 1/2	30 1/2	4,000	2,500	48x36	72x60	16	1 1/2	2	1,100
	6,400	24S40DW	6 1/2	30 1/2	6,400	4,000	48x36	72x60	22	1 1/2	2	1,150
	9,600	24S60DW	6 1/2	30 1/2	7,200	4,500	48x36	72x60	32	1 1/2	4	1,200
	12,000	24S80DW	7 1/4	31 1/4	7,200	4,500	48x36	72x60	44	1 1/2	4	1,400
to 36"	4,000	36S25DW	6 1/2	42 1/2	4,000	2,500	48x48	72x72	24	1 1/2	2	1,300
	6,400	36S40DW	6 1/2	42 1/2	5,600	3,500	48x48	72x72	34	1 1/2	2	1,350
	9,600	36S60DW	6 1/2	42 1/2	5,600	3,500	48x48	72x72	25*	5	4	1,400
	12,000	36S80DW	7 1/4	43 1/4	5,600	3,500	48x48	72x72	35*	5	4	1,650
to 48"	4,000	48S25DW	7	55	4,000	2,500	48x64	72x96	32	1 1/2	2	1,700
	6,400	48S40DW	7	55	5,600	3,500	48x64	72x96	22*	5	2	1,750
	9,600	48S60DW	7	55	5,600	3,500	48x64	72x96	33*	5	4	1,800
	12,000	48S80DW	7 3/4	55 3/4	5,600	3,500	48x64	72x96	45*	5	4	2,100
to 60"	4,000	60S25DW	8	68	4,000	2,500	64x87	96x120	22	5	2	2,400
	6,400	60S40DW	8	68	6,400	3,500	64x87	96x120	44	5	4	2,500
	9,600	60S60DW	8	68	7,200	3,500	64x87	96x120	44	5	4	2,600

Std Power unit is a remote 5hp super torque

to 60"	12,000	60S80DW	12	72	12,000	8,000	64x90	96x120	46	5	4	8,800
	16,000	60S100DW	12	72	16,000	9,000	64x90	96x120	46	5	4	9,000
to 58"	20,000	58S120DW	12 1/2	70 1/2	20,000	10,000	64x90	96x120	72	5	4	9,200
	24,000	58S150DW	12 1/2	70 1/2	22,000	12,000	64x90	96x120	72	5	4	9,400

SPECIFICATIONS: Series 35 Extra Wide Double Long Scissors Lift Model Specifications: Up to 60" x 162"

24"	4,000	24S25EXWDL	30 1/2	6 1/2	4,000	2,500	48x74	72x98	32	1 1/2	4	1,100
	6,400	24S40EXWDL	30 1/2	6 1/2	6,400	4,000	48x74	72x98	32	1 1/2	4	1,150
	9,600	24S60EXWDL	30 1/2	6 1/2	7,200	4,500	48x74	72x98	32	1 1/2	4	1,200
	12,000	24S80EXWDL	31 1/4	7 1/4	7,200	4,500	48x74	72x98	22*	5	4	1,400
36"	4,000	36S25EXWDL	42 1/2	6 1/2	4,000	2,500	48x98	72x122	25*	5	4	1,300
	6,400	36S40EXWDL	42 1/2	6 1/2	5,600	3,500	48x98	72x122	25*	5	4	1,350
	9,600	36S60EXWDL	42 1/2	6 1/2	5,600	3,500	48x98	72x122	25*	5	4	1,400
	12,000	36S80EXWDL	43 1/4	7 1/4	5,600	3,500	48x98	72x122	35*	5	4	1,650
48"	4,000	48S25EXWDL	55	7	4,000	2,500	48x130	72x162	33*	5	4	1,700
	6,400	48S40EXWDL	55	7	5,600	3,500	48x130	72x162	33*	5	4	1,750
	9,600	48S60EXWDL	55	7	5,600	3,500	48x130	72x162	33*	5	4	1,800
	12,000	48S80EXWDL	55 3/4	7 3/4	5,600	3,500	48x130	72x162	45*	5	4	2,100
60"	4,000	60S25EXWDL	68	8	4,000	2,500	58x176	84x206	44	5	4	3,400
	6,400	60S40EXWDL	68	8	5,600	4,000	58x176	84x206	44	5	4	3,500
	9,600	60S60EXWDL	68	8	5,600	4,500	58x176	84x206	44	5	4	3,600

Std Power unit is a remote 5hp super torque

60"	12,000	60S80EXWDL	72	12	12,000	6,000	61x182	90x212	46	5	4	9,600
	16,000	60S100EXWDL	72	12	14,000	10,000	61x182	90x212	46	5	4	9,800
58"	20,000	58S120EXWDL	70 1/2	12 1/2	16,000	12,000	61x182	90x212	72	5	4	10,000
	24,000	58S150EXWDL	70 1/2	12 1/2	20,000	14,000	61x182	90x212	72	5	4	10,200

*Note: Remote 5 hp super torque power units are standard for extra oil volume. **72" and 96" travel models may require guide systems and gates and enclosures. Consult with the factory.

MANUAL TURNTABLES

KEY FEATURES


- 1/2" thick steel platform with radius corners
- Turned, ground, polished & hard-chromed kingpin
- Sealed double row ball bearing rollers
- Rigid base with mounting holes
- Extremely easy to turn
- Factory tested to 110% of capacity
- Safety labels comply with ANSI Z535
- One year warranty

BENEFITS

- Minimal deflection, great durability
- Extended bearing life
- Maintenance free bearings, no greasing required.
- Extremely easy to turn
- Simple to relocate
- Reduced work fatigue
- Exacting standards means it works the first time, every time
- Adds to employee's safety as the turntable meets industry standard for labeling
- Built to last with the best warranty in the industry

CUSTOM DESIGNS

A number of "customized" engineering plans are already on file for the SR Series. Additionally, Autoquip offers computerized engineering services for development of "one-of-a-kind" manual applications.



(Lift not included; sold separately.)

SPECIFICATIONS: 2,500 to 6,000 lb. capacity Rectangular Manual Turntable

Capacity (lbs.)	Series 35 Model No.	Platform Size (in.)	Base Size (in.)	Total Height (in.)	Shipping Weight (lbs.)
2,500	SR4-36-25	36 x 36	24 x 24	4	200
4,000	SR4-36-40	36 x 36	24 x 24	4	200
6,000	SR4-36-60	36 x 36	24 x 24	4	200
2,500	SR4-42-25	42 x 42	24 x 24	4	275
4,000	SR4-42-40	42 x 42	24 x 24	4	275
6,000	SR4-42-60	42 x 42	24 x 24	4	275
2,500	SR4-4248-25	42 x 48	24 x 24	4	300
4,000	SR4-4248-40	42 x 48	24 x 24	4	300
6,000	SR4-4248-60	42 x 48	24 x 24	4	300
2,500	SR4-48-25	48 x 48	24 x 24	4	350
4,000	SR4-48-40	48 x 48	24 x 24	4	350
6,000	SR4-48-60	48 x 48	24 x 24	4	350

SPECIFICATIONS: 2,500 to 6,000 lb. capacity Round Manual Turntable


Capacity (lbs.)	Series 35 Model No.	Platform Size (in.)	Base Size (in.)	Total Height (in.)	Shipping Weight (lbs.)
2,500	SR4R-36-25	36	24 x 24	4	200
4,000	SR4R-36-40	36	24 x 24	4	200
6,000	SR4R-36-60	36	24 x 24	4	200
2,500	SR4R-42-25	42	24 x 24	4	275
4,000	SR4R-42-40	42	24 x 24	4	275
6,000	SR4R-42-60	42	24 x 24	4	275
2,500	SR4R-48-25	48	24 x 24	4	350
4,000	SR4R-48-40	48	24 x 24	4	350
6,000	SR4R-48-60	48	24 x 24	4	350

POWERED TURNABLES

KEY FEATURES

- 1/2" thick steel platform with radius corners
- Turned, ground, polished & hard-chromed kingpin
- Sealed double row ball bearing rollers
- Rigid base with mounting holes
- UL labeled and listed control components
- Factory tested to 110% of capacity
- Safety labels comply with ANSI Z535
- One year warranty

(Lift not included; sold separately.)



BENEFITS

- Minimal deflection, great durability
- Extended bearing life
- Maintenance free bearings, no greasing required. Extremely easy to turn
- Simple to relocate
- High quality and high product life expectancy
- Exacting standards means it works the first time, every time
- Adds to employee's safety as the turntable meets industry standard for labeling
- Built to last with the best warranty in the industry

POWER SUPPLY

- The Power Turntable is powered by a 1/4 hp, 115-230V/ 60 hz/ 1 ph motor. Controls are not supplied as standard.

CUSTOM DESIGNS

A number of "customized" engineering plans are already on file for the SR Series. Additionally, Autoquip offers computerized engineering services for development of "one-of-a-kind" powered turntable applications.

SPECIFICATIONS: 2,500 to 6,000 lb. capacity Rectangular Powered Turntable

Capacity (lbs.)	Series 35 Model No.	Platform Size (in.)	Base Size (in.)	Total Height (in.)	Shipping Weight (lbs.)
2,500	SRP-36-25	36 x 36	24 x 24	10	385
4,000	SRP-36-40	36 x 36	24 x 24	10	385
6,000	SRP-36-60	36 x 36	24 x 24	10	385
2,500	SRP-42-25	42 x 42	24 x 24	10	450
4,000	SRP-42-40	42 x 42	24 x 24	10	450
6,000	SRP-42-60	42 x 42	24 x 24	10	450
2,500	SRP-4248-25	42 x 48	24 x 24	10	485
4,000	SRP-4248-40	42 x 48	24 x 24	10	485
6,000	SRP-4248-60	42 x 48	24 x 24	10	485
2,500	SRP-48-25	48 x 48	24 x 24	10	525
4,000	SRP-48-40	48 x 48	24 x 24	10	525
6,000	SRP-48-60	48 x 48	24 x 24	10	525

SPECIFICATIONS: 2,500 to 6,000 lb. capacity Round Powered Turntable

Capacity (lbs.)	Series 35 Model No.	Platform Size (in.)	Base Size (in.)	Total Height (in.)	Shipping Weight (lbs.)
2,500	SRPR-36-25	36	24 x 24	10	385
4,000	SRPR-36-40	36	24 x 24	10	385
6,000	SRPR-36-60	36	24 x 24	10	385
2,500	SRPR-42-25	42	24 x 24	10	450
4,000	SRPR-42-40	42	24 x 24	10	450
6,000	SRPR-42-60	42	24 x 24	10	450
2,500	SRPR-48-25	48	24 x 24	10	525
4,000	SRPR-48-40	48	24 x 24	10	525
6,000	SRPR-48-60	48	24 x 24	10	525

S35 TILTERS

KEY FEATURES

- Lubricated-for-life composite bearings on all pivot points
- Solid steel platform with stiffener bars
- Turned, ground, polished and hard-chromed axle pins
- Direct thrust cylinders
- Chrome plated cylinder rods
- Double-wire braided hydraulic hoses
- Maintenance (safety) devices
- Polyethylene fluid reservoir
- Factory tested to 110% capacity
- Internally mounted and pre-wired power unit with UL listed components
- Built and designed in accordance with ANSI MH29.2
- Safety labels comply with ANSI Z535
- One year warranty

BENEFITS

- Maintenance-free bearings, no greasing required
- Minimal platform deflection
- Extended bearing life
- Provides the lowest collapsed height
- Corrosion resistance adds to life of cylinder
- Extended hose life for added safety
- Easy servicing of hydraulic components
- Easy inspection for fluid level, condensation and pollutants
- Exacting standards means it works the first time, every time
- Ready-to-operate with zero plumbing and minimal wiring components
- Designed to meet or exceed all industry standards
- Adds to employee's safety as the lift meets all industry standards for labeling
- Built to last with the best warranty in the industry

POWER SUPPLY The electric motor is internally mounted. It is available in either 1 1/2 hp three-phase or 3/4 hp single-phase, with 24V AC control voltage.

CUSTOM DESIGNS

A number of "customized" engineering plans are already on file for the STE Series. Additionally, Autoquip offers computerized engineering services for development of "one-of-a-kind" ergonomic tilter applications.



(Lift not included; sold separately.)

SPECIFICATIONS: 30° to 45° Travel; Capacities 2,500 to 6,000 lbs.

Travel (degrees)	Capacity (lbs.)	Series 35 Model No.	Lowered Height (in.)	Raising or Lowering Time (sec.)	Standard Platform (in.)	Base Size (in.)	Electric Motor (hp)	No. of Cyl.	Shipping Weight (lbs.)
30	2,500	STE 30-25-4	8	5	44 x 44	24 x 41	1.5	1	500
45	2,500	STE 45-25-4	8	8	44 x 44	24 x 41	1.5	1	525
30	2,500	STE 30-25-5	8	5	50 x 50	24 x 41	1.5	1	600
45	2,500	STE 45-25-5	8	8	50 x 50	24 x 41	1.5	1	625
30	4,000	STE 30-40-4	8	5	44 x 44	24 x 41	1.5	1	525
45	4,000	STE 45-40-4	8	8	44 x 44	24 x 41	1.5	1	550
30	4,000	STE 30-40-5	8	5	50 x 50	24 x 41	1.5	1	625
45	4,000	STE 45-40-5	8	8	50 x 50	24 x 41	1.5	1	650
30	6,000	STE 30-60-4	8	5	44 x 44	24 x 41	1.5	1	550
45	6,000	STE 45-60-4	8	8	44 x 44	24 x 41	1.5	1	575
30	6,000	STE 30-60-5	8	5	50 x 50	24 x 41	1.5	1	650
45	6,000	STE 45-60-5	8	8	50 x 50	24 x 41	1.5	1	675