

# 20-DMEGA SERIES PRECISION DUAL SIDE DRIVE



The 20-Omega Series is a cost effective solution for unitized Dual Side drive plasma cutting table. This system features a robust design. With the ability to have up to three tool stations. The Omega is offered with two styles of cutting table's down-draft table or water table. There are two drive packages offer with the Omega, The first is the Hypertherm Edge TI with 250W AC servo drives and 4 axis control and a integrated PHC lifter for the Hypertherm HSD130. The second drive package is the Hypertherm Edge Pro with 400W AC servo drives and the Axis HD-2 THC for use with the Hypertherm HPR130 and HPR260 with Auto Gas Console for a truly integrated package. The Omega is capable of cutting at over 300 ipm and rapid speeds of 940 ipm. The Omega come fully assembled ready to be installed by factory trained technicians on your site, Installation is included in the package price. This machine is Proudly Made in the USA.

#### Specifications

Rapid speed 940 ipm AC drive Low speed 5 ipm Position Accuracy +/- .001" Repeatability +/-.005" **Maximum Stations 3** Parking Area 40"

Power Requirements: 115 VAC AC drives or

230 VAC AC drives

#### **Optional Features**

Hypertherm HSD130 Hypertherm HPR130XD Hypertherm HPR260XD Downdraft dust collectors **Drill Station** Air Scribe Oxy-Fuel Torch

## Standard Features:

Hypertherm<sup>™</sup> Edge Ti<sup>™</sup>or Avaliable Hypertherm<sup>™</sup> Edge Pro<sup>™</sup> 250 Watt AC Servo Drives 400 Watt AC Servo Drives (with Edge Pro) 15" Acoustic Wave Touch Screen Magnetic Brake-away Optional Air Brake-away 25:1 Ratio Planatary Gear Boxes Linear Rails On Y (2) 25 mm Linear Rails On X (2) 15 mm Hypertherm™ HSD130 Standard Plasma 4500 Lbs Table Capacity Choice of Water Or Down Draft Table 12" Ducting on Down Draft Table 24 Pitch 20 PA Gear Rack AGMA Class 8 Pinions and Rack 2.5" 4130 Pinions E-Stop on Gantry and Control High Quality Cable Carriers on X and Y **Heavy Duty Motor Mounts** Phoenix™ V8.5 Software Remote Help 2 USB ports 1 LAN Port Joystick control **Speed Pot EIA** input **DXF** Converter 250 Gigabyte Hard Drive **Built in nesting Software** Integrated THC



Hypertherm Edge Ti



**AC Servo Drives** 





Hypertherm HSD 130 Standard

( Specification Subject to change without notice)



2901 S. Highland Drive Blg -4C Las Vegas, NV 89109
Phone 702-259-6677
Fax 702-361-9612
Web www.axisplasma.com





### **Machine Sizes**

5' X 10' A = 64" B = 124" C = 169.75" D = 204.75" E = 82"

6' X 12' A = 76" B = 148" C = 193.75" D = 229.75" E = 102"

5' X 20' A = 64" B = 244" C = 289.75" D = 325.75" E = 82"

6' X 20' A = 76" B = 244" C = 289.75" D = 325.75" E = 102"

8' X 12' A = 100" B = 148" C = 193.75" D = 325.75" E = 132"

8' X 20' A = 100" B = 244" C = 289.75" D = 325.75" E = 132"



2901 S. Highland Drive Blg -4C Las Vegas, NV 89109 Phone 702-259-6677 Fax 702-361-9612 Web www.axisplasma.com

