PRODUCT SPECIFICATIONS

Better Engineering's GENESIS Series



G-2000 Parts Washer



G-2000 Parts Washer

Two GENESIS Models

The G-2000 and G-3000 represent 30 years of continuous improvement. They revolutionized the industry in the beginning and continue to lead their class today. The G-2000 and G-3000 are designed to give a customer maximum cleaning power in the smallest possible footprint. Features include the roll-in door, a vertical (seal-less) pump, automatic water level controls, jam-free turntable drive system, oil skimmer, slide-out filter basket, etc.

Roll-Away Door

One of the hallmark features of the Genesis parts washers is the roll-away door, which saves floor space. The doors are center supported and don't suffer from the drag problems experienced by doors with outside rollers... hence the LIFETIME GUARANTEE.

Vertical (seal-less) Pumps

The Genesis units have vertical, seal-less pumps. There are no bearings or seals beneath the solution level. The pumps are driven with TEFC motors. The motors have extended shafts that connect directly to the pump impellers (no couplings.)

LIFETIME GUARANTEES

<u>Lifetime Guarantee</u> against any welds cracking or leaking * <u>Lifetime Guarantee</u> on the turntable and its sealed bearing assembly <u>Lifetime Guarantee</u> against the door ever jamming

*Warranty void if leaks caused by corrosion.

Better Engineering's GENESIS Series



G-2000 Parts Washer

Standard Features

Ergonomic 31" Loading Height
Vertical (Seal-less) Pump
Low Water Warning & Shut-Down
Automatic Water Fill
Oil Skimmer
Jam-Proof Turntable Drive
30 Min. Wash Timer
12 Hr. Heat Timer
Mid-Swing Cleaning Manifold
Sealed Cleaning Chamber
Slide-Out Chip Basket

Optional Features

230 V/ 460 V 3-Phase Power
Automatic 7-day/24-hr. Timer
Casters
Brush & Pump for Hand Cleaning
Steam Exhaust
In-Line Strainer
In-Line Bag Filter
Insulation
ZX Upper Turntable

STANDARD SPECIFICATIONS



ZX Upper Turntable

FEATURE	G-2000	G-3000
Turntable Dia.	27"	37"
Working Height	36"	48"
Weight Capacity	500 lbs.	1,500 lbs.
Load Height	31"	31"
Vertical Pump	3 HP	5 HP
Pump Output	60 GPM/45 PSI	100 GPM/50 PSI
Tank Size	55 gal	100 gal
Heat	6 kW	12 kW
Heat-up Time	1.25 hours	1.25 hours
Portable	Optional	N/A
Electric Power	230V/1-Phase	230V/3-Phase
Full Load Amps	49	52
Overall Dims 42"	w x 49"d x 79"h	56"w x 65"d x 94"h
Shipping Weight	800 lbs.	2,000 lbs.