H SERIES

Central Granulators



H Series Granulators Offer High-Capacity Reclamation

The H Series units were developed over many years, to perfect the process of reclaiming purgings, patties, and the extremely heavy cross section material forms. These units feature massive, solid rotors with special staggered knife arrangements, and horsepowers of 200 or more.

The goal of these units is to yield final granulate in a typical range of 0.25 to 0.375 inch, at very high rates. Operating at rotor speeds higher than traditional units, and often configured in cutting chambers that are modified to be water cooled, these units offer steady, dependable performance, for years of durability.

Model	37H	50H	C1000H	C1400H
Throat Size, in.	18x37	20x50	20x40	20x56
Cutting Circle, in.	16	18	18	18
Throughput (3/8" screen)	3000	4000	3000	4000
Infeed	Conveyor			
Cutting Chamber	(2) Bed, Raised Downstroke			
Rotor	15 Knife Helical Hog	18 Knife Helical Hog	15 Knife Helical Hog	21 Knife Helical Hog
Bed Knives	(2) HCHC			
Screen Diameter	3/8"			
Base	Step Type	Step Type	Airveyor	Airveyor
Discharge	Airveyor			
Motor (tefc)	150 hp	200 hp	150 hp	200 hp
Drive	V-Belt			
Electrical Components	Safety switches wired to common junction box			
Controls	To suit voltage - 110V at operator station			
Accessories	Conveyors, blowers, cyclone separators to suit application			
Feed Height, in.	104	112	102	102
Length, in. (mm)	46 (1168)	46 (1168)	87 (2210)	87 (2210)
Width, in. (mm)	117 (2972)	140 (3556)	126 (3200)	148 (3759)
Height, in. (mm)	135 (3429)	164 (4166)	122 (3099)	122 (3099)
Weight (lbs)	12,000	18,000	14,000	17,000


Features

- Internal surfaces machined for ease of clean out and material flow
- Heavy-duty, outboard mounted, double roller bearings
- Designed for high-capacity central reclaim
- 15, 18, 21 and 25-knife rotor
- Handles a wide variety of applications including extruder purgings, sheet pipe scrap and other high torque applications

Helical Hog Rotor (std.) 15, 18, 21 & 25 Knife

Typical Applications:

Ultra thick section purgings up to approx. 6" thick section, slabs, rods, pre-cut pipe, rolls of film



Global Headquarters

Cumberland Schaumburg 1100 E. Woodfield Road Suite 550 Schaumburg, IL 60173 Tel: +1 (262) 641 8600 Fax: +1 (262) 641 8653 Cumberland New Berlin 2900 S 160th Street New Berlin, WI 53151 Tel: +1 (262) 641 8600 Fax: +1 (262) 641 8653

Cumberland Suzhou 109 Xingpu Road SIP Suzhou, China 215126 Tel: +86 512 8717 1919 Fax: +86 512 8717 1916 Cumberland Warsaw ul. Działkowa 115 02-234 Warszawa Tel: +48 22 390 9720

+ 48 22 390 9721 + 48 22 390 9722

Fax: + 48 22 390 9724

Cumberland India

Gat No. 191/1, Sandbhor Complex, Mhalunge, Chakan, Tal Khed, Dist. Pune 410501, India Tel: +91 21 35329112 Fax: +91 20 40147576







