

X-tra 30 H

Elmasonic ultrasonic cleaning unit

Elma Order Nos

| | |
|--|--------------|
| Elmasonic X-tra 30 H (230 V) | 220 030 0000 |
| Elmasonic X-tra 30 H (115 V) | on request |
| Stainless steel cover | 100 1461 |
| Stainless steel basket (mm / inch) 206 x 106 x 52 / 8.1 x 4.2 x 2.0 | 100 1349 |
| Additional accessories on request | |



Pictured X-tra 30 H

The extra league of ultrasonic cleaners “Made in Germany“

- long life through new cavitation-resistant stainless steel tank, with extended warranty for 3 years
- powerful through additional transducer systems
- Sweep – for optimal sound distribution because of electrical oscillation of the sound field
- 2 cleaning modes: “power“ for intensive cleaning, “soft“ for careful cleaning of sensitive materials
- strong heating power for a short heat-up time
- dry-running proof heating elements
- practical handling through appliance inlet
- fast drainage, with welded pipes
- protected operating panel
- timer for ultrasonic activity, variable between 0 and 15 min. and permanent operation
- temperature control 30 - 80 °C

Technical data

| | | | |
|---------------------------------------|------------------------|---------------------------|-----------------|
| Mains voltage (Vac) | 100-120V oder 200-240V | Tank max. volume (litres) | 3,0 |
| Mains connection | 1 Ph. / 1 N / 1 PE | Drain | 3/8" |
| Ultrasonic frequency (kHz) | 35 | Weight (kg) | 7,1 |
| Power consumption total (W) | 540 | Material tank | Stainless steel |
| Ultrasonic power effective (W) | 70 / 120 | Material casing | Stainless steel |
| Ultrasonic peak performance max.* (W) | 480 | Protection class | IP 20 |
| Heating (W) | 400 | | |
| Power frequency (Hz) | 50 / 60 | | |
| Unit outer dimensions W / D / H (mm) | 360 / 205 / 250 | | |
| Tank int. dimensions W / D / H (mm) | 240 / 130 / 100 | | |

* The signal form of the wave results in a factor 4 for the ultrasonic peak max., depending on the modulation of the wave.