

STOP CLEANING WITH A SCRUB BRUSH!

JETSINK[®]

EMC[®] PRESENTS THE FUTURE OF AUTOMATIC PARTS CLEANING

STANDARD FEATURES

- **110 VOLT** "just plug in and clean"
220 & 440 Volt models available.
- **FULLY INSULATED**
No dangerous hot surfaces. Minimal energy usage. Extremely quiet.
- **DUAL 360° SPRAY MANIFOLD**
with 80 precision targeted jets!
- **COALESCING LID** eliminates the need for a steam vent.
- **VERTICAL PUMP** Ultra high volume 80/120 GPM pump. 2" inlet and outlet.
- **LARGE WASH CAPACITY**
26"L x 14"W x 15"T. Larger models available.
- **"V" WASH RACK** automatically positions parts for optimal cleaning.
- **WASH CYCLE TIMER** with lid interlock switch and indicator light.
- **ADJUSTABLE THERMOSTAT**
Panel mounted with indicator light.
- **U.L. LISTED/RECOGNIZED COMPONENTS**
- **OIL SKIMMER** to dramatically extend solution life.
- **SMALL PARTS BASKET**
- **RUGGED ALL STEEL CONSTRUCTION**
- **OPTIONS:**
 - Stainless Steel construction
 - Casters ■ Work Station ■ Parts Baskets
 - Rotary Tumble Basket to wash, de-water and dry delicate small parts and hardware
 - Dip Tank with 'agitate or soak' feature

Scrubbing with a brush at work? Automatic washing at home?

Perhaps you like the solvent, grime, and fumes! Could it be the hours of menial labor to produce poorly cleaned parts? What about the hazards and health effects of flammable solvent on your hands, your clothes, and the floor? The **JETSINK** will clean all your parts for less while eliminating the mess, liability, and labor costs!



JETSINK[®] Model 1426

SHOWN WITH OPTIONAL DIP TANK BASKET
AND WORK STATION PARTS TRAY.

HOW THE JETSINK® WORKS

The **EMC JETSINK** all purpose automatic **CLEANING STATION™** is simple to use and maintain. Just plug it in, fill with water & soap, allow the unit to initially heat up, load the parts to be cleaned, and turn on the pump. In as little as 30 seconds most oily and greasy parts are clean.

Choose the optional Rotary Tumble Basket system to spray wash, de-water, and dry quantities of delicate small parts and hardware. For intricate and difficult to clean parts, choose the Dip Tank Basket option for submerged 'agitate or soak' cleaning. Both of these options can operate at the same time and still allow regular wash loads...it's like three machines in one!

For high volume and heavy soil applications, the 220/440 volt model provides added cleaning action and other ease-of-use features. Included are a 120 GPM high psi pump, 13,500 watt Heating System for quick startup, and 7 Day Heating Cycle Timer.



**JUST LOAD YOUR
PARTS IN THE
WASH RACK – THE
JETSINK
DOES THE REST!**



U.S. Patent #5,730,872
other Patent(s) pending

JETSINK®	MODEL 1426 110V.	MODEL 1426 220/440V.
FLOOR SPACE	38" L X 20" W X 37" T (work station 24" x 17")	38" L x 20" W x 37" T (work station 24" x 17")
CONSTRUCTION	12 Gauge Tank 16 Gauge Skin Fully Insulated	12 Gauge Tank 16 Gauge Skin Fully Insulated
PUMP	80 GPM, Centrifugal	120 GPM, High PSI Centrifugal
DRAIN	1" NPT with full- port ball valve	1" NPT with full- port ball valve
MAXIMUM LOAD SIZE	14" x 26" x 15" T (Dip Tank 9" x 21" x 8.5") (Rotary 8 x 8 x 18)	14" x 26" x 15" T (Dip Tank 9" x 21" x 8.5") (Rotary 8 x 8 x 18)
WEIGHT CAPACITY	500 lbs. (work station 200 lbs.)	500 lbs. (work station 200 lbs.)
FLUID CAPACITY	25 Gallons	25 Gallons
HEATING SYSTEM	1650 Watts	13,500 Watts with 7 day timer
ELECTRIC	110V.13Amp	220V/3/40Amp. (Convertible to 1 Ph) 440V/3/20Amp.
SHIP WEIGHT	350 lbs.	350 lbs.

POWERJET® AUTOMATIC PARTS WASHERS ■ WATER EATER® WASTEWATER EVAPORATOR

MANUFACTURED BY:

FOR SALES INFORMATION:

EMC®

EQUIPMENT MANUFACTURING CORPORATION

14930 Marquardt Avenue ■ Santa Fe Springs, CA ■ 90670 ■ U.S.A.
(888) 833-9000 ■ (562) 623-9394 ■ Fax (562) 623-9342
www.equipmentmanufacturing.com

(6/00) Printed in USA
copyright 2000