



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G8621 SLIDING TABLE SHAPER

Product Dimensions:

Weight..... 720 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 34-3/4 x 35-1/2 x 45-1/2 in.
Footprint (Length x Width)..... 25-1/2 x 26-3/4 in.

Shipping Dimensions:

Type..... Wood Crate
Content..... Machine
Weight..... 757 lbs.
Length x Width x Height..... 40 x 30 x 44 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 220V, Single-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 25A
Minimum Circuit Size..... 30A
Connection Type..... Cord & Plug
Power Cord Included..... No
Recommended Power Cord..... "S"-Type, 4-Wire, 10 AWG, 300 VAC
Recommended Plug Type..... L15-30
Switch Type..... Control Panel w/Magnetic Switch Protection

Motors:

Main

Type..... TEFC Capacitor-Start Induction
Horsepower..... 5 HP
Phase..... Single-Phase
Amps..... 25A
Speed..... 3450 RPM
Power Transfer Belt Drive
Bearings..... Shielded & Permanently Lubricated

Main Specifications:

Operation Info

Max. Cutter Height..... 5 in.
Max. Cutter Dia..... 5-7/8 in.
Spindle Sizes..... 3/4, 1, 1-1/4 in.
Spindle Lengths..... 6-7 in.
Exposed Spindle Length..... 7-3/8 in.
Spindle Cap Under The Nut..... 4-1/4, 4-5/8, 5-1/8 in.
Spindle Speeds..... 3600, 5100, 8000, 10,000 RPM
Spindle Travel..... 3-1/4 in.
Spindle Openings..... 2, 3, 3-1/2, 7 in.

Table Info

No. of Table Inserts.....	3
Table Insert Sizes I.D.....	2, 3, 3-1/2 in.
Table Insert Sizes O.D.....	3, 3-1/2, 7 in.
Table Counterbore Diameter.....	7 in.
Table Counterbore Depth.....	5/8 in.
Table Size Length.....	35-1/2 in.
Table Size Width.....	14-7/8 in.
Table Size Thickness.....	3-5/16 in.
Floor To Table Height.....	34-3/4 in.
Overall Width With Table Extd.....	56-1/2 in.
Table Fence Length.....	39-1/2 in.
Table Fence Width.....	19/32 in.
Table Fence Height.....	4-1/4 in.

Sliding Table Info

Sliding Table Travel.....	21-7/8 in.
Sliding Table Size Length.....	35-1/2 in.
Sliding Table Size Width.....	13-1/4 in.
Sliding Table Size Thickness.....	2 in.

Miter Gauge Info

Miter Angle.....	0 – 60 deg. L/R
------------------	-----------------

Construction

Table.....	Precision-Ground Cast Iron
Body Assembly.....	Cast Iron
Cabinet.....	Formed Steel
Fence.....	Cast Iron with Wood
Miter Gauge.....	Cast Iron
Guard.....	Cast Iron
Spindle Bearings.....	Sealed & Lubricated
Paint.....	Powder Coated

Other

No. of Dust Ports.....	1
Dust Port Size.....	4 in.
Mobile Base.....	D2058A

Other Specifications:

Country Of Origin	Taiwan
Warranty	1 Year
Approximate Assembly & Setup Time	45 Minutes
Serial Number Location	ID Label on Stand
ISO 9001 Factory	No
CSA Certified	No

Features:

Miter Angle Adjustable 60 deg. Left to 60 deg. Right
Precision Ground Cast Iron Table
Green Epoxy Paint
Fence Adjustment Includes Built-In Ratchets and Knob-Equipped Adjusters
Extruded Aluminum Miter Fence with Adjustable Stop Block
Lever-Actuated Stock Hold-Down
Spindles Include Spacer and Nuts
Spindle Height Scale in Inches and Millimeters
Sliding Table Rides on Eight Shielded and Lubricated Ball Bearings
3 Table Inserts
4 Spring Steel Hold-Down Assemblies