



Models 6629, 6639
Models 6649, 6659 are Flange Mount

Specifications (Unit: inch)

Model No.	Thrust Adv./Ret. @ 1000 psi	Stroke	Quill Dia.	Max. Spindle Speed	Min. Spindle Speed	Retract Feed	Depth Repeat-ability
6629*	3000/3000	6"	3.500"	5000	80	Programmable	+/- .0005
6639**	3000/3000	6"	3.500"	5000	80	Programmable	+/- .0005
6649*	3000/3000	6"	3.500"	5000	80	Programmable	+/- .0005
6659**	3000/3000	6"	3.500"	5000	80	Programmable	+/- .0005

* Denotes Tempsonic probe

** Denotes Sony encoder feedback

Features

- Full programmability.
- Belt housing/position choices.
- Various spindle and drive choices.
- Pulley and RPM choices.
- Other options available.

All models can be used vertically or horizontally.

Customizing A Hause Unit To Your Specs

Most Hause power feed units can be customized to best fit the needs of your unique applications. Using the worksheet at the back of this catalog and the information found on pages 36 - 49, you can spec out the Hause unit of your choice.

Model	Spindle	Drive	Belt/Pulley	Motor	Belt Housing	Special
6629	-	BE	-	N	-	N/A
	Pgs. 36-37	Pgs. 38-39	Pgs. 40-41	Pgs. 42-44	Pg. 45	Pgs. 46-49

Example: 6629-BE-N-N/A-Q-C3 This code specifies a Hydraulic Drilling unit (Model No. 6629) with a 6" stroke. Accessorizing this unit is a 1-1/16" Adjustable Adapter Spindle, 1-1/8" Direct Drive, no Belt/Pulley system, a 3 HP (1800 RPM) Nema "C" Flange Mounted Motor. No Belt Housing required.