

HEM Dual Column: CT2000HA-DC-C

Capacity: 20" W x 20" H • Blade: 2" x 22'2" x .063" • Motor: 20 HP

Hydraulics: 2 HP • Bar-feed: 0-24" (Multiple Index)



Standard Features

Swing-Away Console – All Function Control
2° Permanent Arm Tilt
Hydraulic Computer Controlled Traverse (HCCT)
24" Solid Discharge Table
Full Stroking Vises w/ Adjustable Clamping Force
Carbide Blade Guides
Lead In/Lead Out Roller Guides
Computer Controlled Feed System
Adjustable Blade Speed w/ LED Readout
Powered Blade Tension
Cut Watcher System
Powered Guide Arm
Chip Auger System
Height Adjusted from Console
3rd Holding Vise on Feed & Material Jogging
Shadow Light System
Blade Brush
Flood Coolant System w/ Wash-Down Hose
Safety Lockout Key
Broken Blade & Out of Stock Indicators
Safety Guards
220V/440V/3PH Electrical Motor Requirement
– This is Not a Dual Voltage Machine

Proudly Made in the U.S.A.



Optional Features

0-48" Stroke Bar-Feed
0-72" Stroke Bar-Feed w/ 3rd Holding Vise
Full Capacity Top Clamp – Main & Feed Vise
Full Capacity Top Clamp – Outboard Vise
Interlocking Vise Jaws
Laser Light System
Outboard Powered Vise on Discharge
Spray Mist Lubrication
Left Side Swing-Away Console
Pedestal Mounted Console
Free Standing Console
5' or 10' Discharge Table Extension
Idle or Powered Roller Stock Tables



www.hemsaw.com

Address: P.O. Box 1148 Pryor OK 74361 • **Toll Free:** 888-729-7787 • **Email:** info@hemsaw.com

HEM, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact HEM, Inc. for a certified dimensional drawing of your specific model.
Copyright 112800 HEM, Inc. All rights reserved.