HEM Dual Column: H160A-DC-C

Capacity: 25″ W x 25″ H • **Blade:** 2” x 22’0″ x .063″ • **Motor:** 20 HP
Hydraulics: 5 HP • **Bar-feed:** 0-24″ (Multiple Index)



Proudly Made in the U.S.A.

Standard Features

Swing-Away Console – All Function Control
Computer Controlled Feed System
24″ Roller Discharge Table
3rd Holding Vise on Feed
Full Stroking Vises
Adjustable Clamping Force
Lead In/Lead Out Roller Guides
Adjustable Cutting Force & Feed Rate
Carbide Blade Guides
Cut Watcher System
Powered Guide Arm
Push Button Blade Speed w/ LED Readout
Blade Brush
Height Adjusted from Console
Powered Blade Tension
Chip Auger System
Flood Coolant System w/ Wash-Down Hose
Safety Lockout Key
Broken Blade & Out of Stock Indicators
220V/440V/3PH Electrical Motor Requirement

Optional Features

Hydraulic Computer Controlled Traverse (HCCT)
2-5/8″ Blade Option – HD Gear Box
0-72″ Stroke Bar-Feed w/ 3rd Holding Vise
24″ Solid Discharge Table (In Lieu of Rollers)
Full Capacity Top Clamp – Main Vise Only
Full Capacity Top Clamp – Main & Feed Vise
Full Capacity Top Clamp – Outboard Vise
Interlocking Vise Jaws
Shadow Light System or Laser Light System
Outboard Powered Vise on Discharge
Spray Mist Lubrication
Optional Consoles
5′ or 10’ Discharge Table Extension
Idle or Powered Roller Stock Tables

H&M® SAW
The saw that cuts straight.

www.hemsaw.com

Address: P.O. Box 1148 Pryor OK 74361 • **Toll Free:** 888-729-7787 • **Email:** info@hemsaw.com

HEM, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact HEM, Inc. for a certified dimensional drawing of your specific model.
Copyright 112800 HEM, Inc. All rights reserved.