

HEM Dual Column: H160LM-DC

Capacity: 30" W x 25" H • Blade: 2" x 23'0" x .063" • Motor: 20 HP • Hydraulics: 5 HP



**Shown w/ Optional Chip Auger*

Proudly Made in the U.S.A.

Standard Features

- Swing-Away Console – Semi-Automatic Control
- 24" Roller Discharge Table
- Full Stroking Main Vise
- Adjustable Clamping Force
- Lead In/Lead Out Roller Guides
- Adjustable Cutting Force
- Adjustable Feed Rate
- Carbide Blade Guides
- Cut Watcher System
- Powered Guide Arm
- Push Button Blade Speed w/ LED Readout
- Blade Brush
- Height Adjusted from Console
- Powered Blade Tension
- Flood Coolant System w/ Wash-Down Hose
- Safety Lockout Key
- Broken Blade Indicator
- Safety Guards
- 220V/440V/3PH Electrical Motor Requirement



Optional Features

- Outboard Powered Vise on Discharge
- Full Capacity Top Clamp – Main Vise
- Full Capacity Top Clamp – Outboard Vise
- 24" Solid Discharge Table (In Lieu of Rollers)
- Hydraulic Computer Controlled Traverse (HCCT)
- 2-5/8" Blade Option – HD Gear Box
- Chip Auger System
- Laser Light System
- Shadow Light System
- Spray Mist Lubrication
- Left Side Swing-Away Console
- Free Standing Console
- Pedestal Mounted Console
- 5' or 10' Discharge Table Extension
- Idle or Powered Roller Stock Tables

HEM[®] SAW
—The saw that cuts straight.—

www.hemsaw.com

Address: P.O. Box 1148 Pryor OK 74361 • **Toll Free:** 888-729-7787 • **Email:** info@hemsaw.com

HEM, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact HEM, Inc. for a certified dimensional drawing of your specific model.
Copyright 112800 HEM, Inc. All rights reserved.