

# HEM Dual Column: H160XLA-DC-C

**Capacity:** 36" W x 25" H • **Blade:** 2" x 24'0" x .063" • **Motor:** 20 HP  
**Hydraulics:** 5 HP • **Bar-feed:** 0-24" (Multiple Index)



**Proudly Made in the U.S.A.**

## **Standard Features**

Swing-Away Console – All Function Control  
Computer Controlled Feed System  
24" Roller Discharge Table  
3rd Holding Vise on Feed  
Full Stroking Vises  
Adjustable Clamping Force  
Lead In/Lead Out Roller Guides  
Adjustable Cutting Force & Feed Rate  
Carbide Blade Guides  
Cut Watcher System  
Powered Guide Arm  
Push Button Blade Speed w/ LED Readout  
Blade Brush  
Height Adjusted from Console  
Powered Blade Tension  
Chip Auger System  
Flood Coolant System w/ Wash-Down Hose  
Safety Lockout Key  
Broken Blade & Out of Stock Indicators  
220V/440V/3PH Electrical Motor Requirement



## **Optional Features**

Hydraulic Computer Controlled Traverse (HCCT)  
2-5/8" Blade Option – HD Gear Box  
0-72" Stroke Bar-Feed w/ 3rd Holding Vise  
24" Solid Discharge Table (In Lieu of Rollers)  
Full Capacity Top Clamp – Main Vise Only  
Full Capacity Top Clamp – Main & Feed Vise  
Full Capacity Top Clamp – Outboard Vise  
Interlocking Vise Jaws  
Shadow Light System or Laser Light System  
Outboard Powered Vise on Discharge  
Spray Mist Lubrication  
Optional Consoles  
5' or 10' Discharge Table Extension  
Idle or Powered Roller Stock Tables



**www.hemsaw.com**

**Address:** P.O. Box 1148 Pryor OK 74361 • **Toll Free:** 888-729-7787 • **Email:** info@hemsaw.com

HEM, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact HEM, Inc. for a certified dimensional drawing of your specific model.  
Copyright 112800 HEM, Inc. All rights reserved.