HEM Dual Column: H160XLM-DC

Capacity: 36″ W x 25″ H • **Blade:** 2” x 24’0″ x .063″ • **Motor:** 20 HP • **Hydraulics:** 5 HP



*Shown w/ Optional Chip Auger

Proudly Made in the U.S.A.

Standard Features

Swing-Away Console – Semi-Automatic Control
24″ Roller Discharge Table
Full Stroking Main Vise
Adjustable Clamping Force
Lead In/Lead Out Roller Guides
Adjustable Cutting Force
Adjustable Feed Rate
Carbide Blade Guides
Cut Watcher System
Powered Guide Arm
Push Button Blade Speed w/ LED Readout
Blade Brush
Height Adjusted from Console
Powered Blade Tension
Flood Coolant System w/ Wash-Down Hose
Safety Lockout Key
Broken Blade Indicator
Safety Guards
220V/440V/3PH Electrical Motor Requirement

Optional Features

Outboard Powered Vise on Discharge
Full Capacity Top Clamp – Main Vise
Full Capacity Top Clamp – Outboard Vise
24″ Solid Discharge Table (In Lieu of Rollers)
Hydraulic Computer Controlled Traverse (HCCT)
2-5/8″ Blade Option – HD Gear Box
Chip Auger System
Laser Light System
Shadow Light System
Spray Mist Lubrication
Left Side Swing-Away Console
Free Standing Console
Pedestal Mounted Console
5′ or 10’ Discharge Table Extension
Idle or Powered Roller Stock Tables

HEM® SAW
The saw that cuts straight.

www.hemsaw.com

Address: P.O. Box 1148 Pryor OK 74361 • **Toll Free:** 888-729-7787 • **Email:** info@hemsaw.com

HEM, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact HEM, Inc. for a certified dimensional drawing of your specific model.
Copyright 112800 HEM, Inc. All rights reserved.