

HEM Horizontal Pivot: H90A-4

Capacity: 12.75" W x 12.75" H • **Blade:** 1" x 12'10" x .035"

Motor: 3 HP • **Bar-feed:** 0-24" (4 Indexes)



Standard Features

Easy View Console – All Function Control
24" Solid Discharge Table – Bolts to Saw
Adjustable Main & Feed Vise
Adjustable Clamping Force
2 Hold Down Fixtures
Manual Guide Arm Adjustment
Push Button Blade Speed w/ LED Readout
Adjustable Cutting Force & Feed Rate
Carbide Blade Guides
Cut Watcher System
Manual Blade Tension
Vertical Alignment Bar on Feed
Blade Brush
Flood Coolant System w/ Wash-Down Hose
Broken Blade & Out of Stock Indicators
Safety Guards

220V/440V/3PH Electrical Motor Requirement
– This is Not a Dual Voltage Machine
85 PSI, 4-6 CFM Minimum Air Requirement
(Equipped w/ Air Filter/Lubricator)

Proudly Made in the U.S.A.



Optional Features

Reduced Capacity Top Clamp – Feed Vise
Reduced Capacity Top Clamp – Main Vise
3rd Holding Vise on Feed w/ Interlocking Vise Jaws
Hold-Down Roller Assembly
Interlocking Vise Jaws Only
Spray Mist Lubrication
Pedestal Mounted Console
5' or 10' Idle Roller Stock Table

HEM[®] SAW
—The saw that cuts straight.—

www.hemsaw.com

Address: P.O. Box 1148 Pryor OK 74361 • **Toll Free:** 888-729-7787 • **Email:** info@hemsaw.com

HEM, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact HEM, Inc. for a certified dimensional drawing of your specific model.
Copyright 112800 HEM, Inc. All rights reserved.