

HEM Vertical: VT120HM-60

Capacity: 18" w x 24" h @ 90° • 18" w x 16" h @ 45° L • 18" w x 14.75" h @ 45° R
18" w x 10" h @ 60° L • 18" w x 9" h @ 60° R • **Blade:** 1-1/4" x 16'6" x .042" • **Arm Cant:** 4°
Motor: 7.5 HP • **Hydraulics:** 5 HP

Proudly Made in the U.S.A.



**Shown w/ Optional 2nd Vise*

Standard Features

- Swing-Away Console – Semi-Automatic Control
- Full Stroking Main Vise
- Adjustable Clamping Force
- Powered Tilt w/ Angle Readout
- Push Button Blade Speed w/ LED Readout
- Electronic Controlled Traverse
(Controls Feed Rate & Cutting Force)
- Blade Brush
- Carbide Blade Guides
- Powered Blade Tension
- Powered Guide Arm
- Idle Base Rollers – 1 Each Side of Base
- Flood Coolant System w/ Wash-Down Hose
- Broken Blade Indicator
- Safety Lockout Key & Safety Guards

220V/440V/3PH Electrical Motor Requirement

Optional Features

- Reduced Capacity Top Clamp – Main Vise
- Swing-Away Top Clamp – Main Vise
- 2nd Main Vise
- Cut Watcher System
- Laser Light System
- Power Raised Lift Up Rollers
- Manual Hand-Crank Chip Conveyor
- Powered Chip Conveyor
- Spray Mist Lubrication
- Idle & Powered Load Tables
- Idle & Powered Discharge Tables

HEM[®] SAW
—The saw that cuts straight.—

www.hemsaw.com

Address: P.O. Box 1148 Pryor OK 74361 • **Toll Free:** 888-729-7787 • **Email:** info@hemsaw.com

HEM, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact HEM, Inc. for a certified dimensional drawing of your specific model.
Copyright 112800 HEM, Inc. All rights reserved.