

HEM Wide Flange: WF160LM-DC

Capacity: 30" W x 25" H • Blade: 2" x 26'9" x .063"

Motor: 15 HP • Hydraulics: 5 HP



**Shown w/ Optional Top Clamps & Chip Conveyor*

Standard Features

- Swing-Away Console – Manual Control
- 24" Roller Discharge Table
- 9.2° Permanent Arm Tilt
- Full Stroking Bi-Directional Main Vise
- Adjustable Clamping Force
- Push Button Blade Speed w/ LED Readout
- Adjustable Cutting Force
- Adjustable Feed Rate
- Blade Brush
- Carbide Blade Guides
- Lead In/Lead Out Roller Guides
- Guide Cap Camlocks
- Height Adjusted from Console
- Powered Blade Tension
- Powered Guide Arm
- Flood Coolant System w/ Wash-Down Hose
- Broken Blade Indicator
- Safety Lockout Key
- Safety Guards

220V/3PH or 440V/3PH Electrical Motor Requirement
– This is Not a Dual Voltage Machine

Proudly Made in the U.S.A.



Optional Features

- Full Capacity Top Clamp – Main Vise
- Full Capacity Top Clamp – Outboard Vise
- Bi-Directional Outboard Powered Vise
- Hydraulic Computer Controlled Traverse (HCCT)
- 2-5/8" Blade Option
- Chip Conveyor System
- Cut Watcher System
- Laser Light System or Shadow Light System
- Spray Mist Lubrication
- Optional Control Consoles
- 5' or 10' Discharge Table Extension
- Idle or Powered Roller Stock Tables



www.hemsaw.com

Address: P.O. Box 1148 Pryor OK 74361 • **Toll Free:** 888-729-7787 • **Email:** info@hemsaw.com

HEM, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact HEM, Inc. for a certified dimensional drawing of your specific model.
Copyright 112800 HEM, Inc. All rights reserved.