



NANTONG JUGAO MACHINERY COLTD

ADD: LIBAO INDUSTRY PARK HAIAN COUNTRY JIANGSU PROVINCE CHINA POST

CODE:226600

TEL: 0086513-88283988 FAX:51388932366 MOBILE:008613222111178

E-MAIL: INFO@NTJUGAO.COM WWW.NTJUGAO.COM

Hydraulic guillotine technical data

A、Conventional Standard Lathe

1, Type:CK6150-1000

Machinery

Leading manufacturer

In China



High Quality

Competitive price

Best service



2、Brand: JUGAO. TOP RANKING QUALITY



CE certification brand



CE certification brand

WORLD CLASS

21,000 square meters
Workshops

WORLD CLASS

to ensure high-quality machines



WITNESS THE

STRENGTH

Monthly production
capacity reached 500

The strength witness
Industry-leading scale



360° PLEASANT EXPERIENCE



JUGAO
YOU CAN TRUST

360° Pleasant experience
Attentive service

NANTONG JUGAO

FOR MACHINES, WE ARE MORE PROFESSIONAL QUALITY

B、Performance

1. Diameter of inner hole in main spindle is big. It is with three supports structure. The world famous band shaft bearing. It can bear big pressure and with high precision cutting.

2. The guideway of machine is made from wear-resistant steel. It have been with quenching treatment. And the foot of the machine is whole.

3. The shield of machine is enclosed fully. Frequency control and motor speed motor for machine main drive. Stepless speed regulation.

4. Controller of machine is made from SIEMENS and FANUC. It can supply high efficiency and precision turning processing for round shape, cone shape, sphere shape, thread shape and all kinds of curve rotary shape products.

5. The layout of machine is rational. The appearance of machine is beautiful. The controller of machine is easy. Machine is with high efficiency, high precision, high rigidity capacity. It is used in all kinds of dishes, axial products, complex parts producing.

Application:

1. It can supply high efficiency and precision turning processing for round shape, cone shape, sphere shape, thread shape and all kinds of curve rotary shape products.

2. It is used in all kinds of dishes, axial products, complex parts producing.

MORE COMPETITIVE PRICE.WELCOME TO OUR COMPANY

D、Technical data

SPECIFICATIONS	CK6150
Max. swing dia. over bed	520MM
Max. cutting dia.	340MM
Max. swing dia. over table	350MM
Max. distance between centers	530 / 1000MM
Spindle speed	35-3500r/min
Max. longitudinal stroke	590/1060mm
Max. cross stroke	185mm
Rapid feed for axis X	15m/min
Rapid feed for axis Z	18m/min
Spindle taper	ASA:350#
Spindle bore	80mm
Bore of hydraulic chuck	50mm
Dia./stroke of tailstock sleeve	85/90mm
Taper hole of tailstock sleeve	MT3
Number of tools	12piece
Max. dia of boring shank	50mm
Spindle motor power	15/18.5kw
Min. input unit(X/Z)	0.001/0.001
Overall dimensions (L×W×H)	2970×1540/3690×1540MM
Net Weight	4500/5200KG

EXCELLENT QUALITY, RELIABLE

E: Photos about our lathe machines



JUGAO MACHINERY,HEART SERVICES

Working power can be chosed

- 1.220V 50HZ 3phase
- 2.220V 60HZ 3phase
- 3.240V 50HZ 3phase
- 4.240V 60HZ 3phase
- 5.240V 50HZ 3phase
- 6.240V 60HZ 3phase
7. 200V 50HZ 3phase
- 8.200V 60HZ 3phase
- 9..380V 50HZ 3phase
- 10.380V 60HZ 3phase
- 11.400V 50HZ 3phase
- 12.400V 60HZ 3phase
- 13.415V 50HZ 3phase
- 14.415V 60HZ 3phase
- 15.440V 50HZ 3phase
- 16.440V 60HZ 3phase

F: Warranty

100% warranty for one year.

G: Delivery time:

In 30days after seller receive the deposit.

H:Remittance Information

Account Bank: BANK OF CHINA LTD.,HAIAN SUB-BRANCH

SWIFT CODE: BKCHCNBJ95G

Bank Add: 18 Changjiang Rd(m), Haian, Nantong, Jiangsu, China 226600

Beneficiary: NANTONG JUGAO MACHINERY CO.,LTD.

A/C NO.: 535258233084

Note: The copyright of this document belong to NATNONG JUGAO

NANTONG JUGAO MACHINERY CO.,LTD(Techonogy Department)

Service Hotline: 008651388932366