



NANTONG JUGAO MACHINERY COLTD

ADD: LIBAO INDUSTRY PARK HAIAN COUNTRY JIANGSU PROVICE CHINA

POST CODE:226600

TEL: 008651388283988 FAX:0086513-88932366 MOBILE:008613222111178

E-MAIL: INFO@NTJUGAO.COM WWW.NTJUGAO.COM

Plate roller technical data

A、 machine model name

1、 Type: W11-12X2500

<p>Machinery</p> <p>Leading manufacturer In China</p>	
	
<p>High Quality</p> <p>Competitive price</p> <p>Best service</p>	

2、Brand: JUGAO. TOP RANKING QUALITY




WORLD CLASS

21,000 square meters
Workshops

WORLD CLASS ←

to ensure high-quality machines



WITNESS THE

STRENGTH

Monthly production
capacity reached 500

→ **The strength witness**

Industry-leading scale








360° PLEASANT EXPERIENCE

JUGAO

YOU CAN TRUST

360° Pleasant experience ←

Attentive service

NANTONG JUGAO




B、Performance

1. The Function and Application Scope of the Machinery

This is three-roller symmetric rolling equipment. It is mainly used in the process of cold working in which the sheets within the thickness of 8mm can be bent into different diameter cylindrical tubes. It is widely used in boiler, chemical industry, mining, construction, shipbuilding and other machinery industry.

2、The machine consists of two parts, the operation part and the transmission part which are welded at the whole bottom pallet. The operation part consists of left and right bearing housing, one upper roller, two lower rollers, lifting gears and some accessories. The lower roller is the main one, upper roller can be adjusted at the height. The transmission part consists with the main motor, speed-reducing motor and other accessories.

3、The lower roller is driven by the main motor through the main reduce. The main reductor output shaft transmits to the two lower rollers through a group of gear wheel. The roller driving direction is switched by the main motor.

4、The rise and fall movement of the upper roller is realized by the auxiliary motor through the auxiliary reductor, which drives worm and worm wheel under the left and right roller bearing to move automatically, makes the steel wire nut which is fixed on the worm wheel rotating, and completed by up and down movement of ball bearing screws accordingly.

MORE COMPETITIVE PRICE.WELCOME TO OUR COMPANY

C、Technical data

NO.	Name		Data	Unit	Remark
1	Max rolling thickness		12	mm	MILD STEEL
2	Max rolling width		2500	mm	
3	Yield strength of the sheet		245	Mpa	
4	Rolling speed		4	M/min	
5	Diameter of upper roller		290	mm	
6	Diameter of down rollers		150	mm	
7	Distance between down rollers		245	mm	
8	Motor		11	kw	
9	Dimension	Length	3000	mm	
		Width	1800	mm	
		Height	1600	mm	

QUALITY MACHINES, QUALITY SERVICE

D: The main components supporting manufacturers



This first-class quality assurance

Opinion Parts:

End Roller



End Roller



Material supply equipments



Material supply equipments



Round shape product welding part



Round shape product welding part



QUALITY QUARANTEED.SERVICE FORMOST

Controller



E: Warranty

100% warranty in five years.

F: Delivery time:

In 30days after seller receive the deposite.

G:Remittance Information

Account Bank: BANK OF CHINA LTD.,HAIAN SUB-BRANCH

SWIFT CODE: BKCHCNBJ95G

Bank Add: 18 Changjiang Rd(m), Haian, Nantong, Jiangsu, China 226600

Beneficiary: NANTONG JUGAO MACHINERY CO.,LTD.

A/C NO.: 535258233084

Note: The copyright of this document belong to NATNONG JUGAO.

NANTONG JUGAO MACHINERY CO.,LTD(Techonogy Department)

Service Hotline: 008651388932366

WWW.NTJUGAO.COM