## 203 AND 72 SERIES HORIZONTAL AUTO TIE BALERS



Powerful High Density Balers for the Most Demanding Applications



Maren is the gold standard for powerful, reliable, and durable balers. Maren 203 and 72 series balers provide fast, efficient baling with versatility.

### Versatile to suit your application

- Completely unattended operation
- Wide range of bale cross-sections and in-feed hopper sizes available
- Advanced Automatic Tying (no hydraulics)
- Variable-length baling to meet storage and shipping requirements
- Manufactured with brand name components
- Full range of options available for all models
- Available as a stand alone unit, or as part of a complete baling system (pneumatic scrap system, conveyor feed or cart tipper)

Big On Power.
Engineered with Innovation.
Built to Last.

# Maren balers can handle it

- Box Manufacturing Plants
- Printers
- Document Destruction
   Centers
- Paper Converters
- Tissue & Paper Mills
- Distribution Centers
- Manufacturing Plants
- Breweries

Virtually any scrap material!

U.S.: 800.875.1038 Canada: 800.678.9516 www.marenengineering.com

#### Printers - Paper Converters - Box Plants - Document Destruction - Paper Mills

720E-X-30R

72T-C-25R

12 001100	121-0-23H	120L-X-30H	120E-3-X-40H
Bale Size	30"W x 30"H x variable length	30"W x 40"H x variable length	30"W x 40"H x variable length
Bale Tier	4 wire tie automatic	5 wire tie automatic	5 wire tie automatic
Feed Opening	30"W x 30"L nominal	30"W x 30"L nominal	30"W x 40"L nominal
Operating Pressure	2,600 psi.	2,600 psi.	2,600 psi.
Platen Force	76,000 lbs.	100,000 lbs.	100,000 lbs.
Cylinder	6"	7"	7"
No-load Cycle	10 second*	7.5 second*	7.5 second*
Motor	25hp T.E.F.C 3/60/460VAC	30hp T.E.F.C 3/60/460VAC	40hp T.E.F.C 3/60/460VAC
Shipping Weight:	14,500 lbs.**	17,000 lbs.**	17,000 lbs.**
203 Series	203-103-C-30R	203-103-X-30R	203-103-S-J-100R
Bale Size	30"W x 30"H x variable length	30"W x 40"H x variable length	36"W x 40"H x variable length
Bale Tier	4 wire tie automatic	5 wire tie automatic	5 wire tie automatic
Feed Opening	30"W x 30"L nominal	30"W x 30"L nominal	30"W x 40"L nominal
Operating Pressure	2,700 psi.	2,700 psi.	2,700 psi.
Platen Force	135,000 lbs.	135,000 lbs.	212,000 lbs.
Cylinder	8"	8"	10"
No-load Cycle	10 second*	10 second*	7.5 second*
Motor	30hp T.E.F.C 3/60/460VAC	30hp T.E.F.C 3/60/460VAC	Twin 50hp T.E.F.C. 3/60/460VAC
Shipping Weight:	23,000 lbs.**	25,000 lbs.**	30,000 lbs.**

### **Distribution Centers - Breweries - Manufacturing Facilities** Wide

<b>Mouth Shear</b>	SWSS-A-7-AT30R	SWSS-A-8-AT60R	203-338-C-80R
Bale Size	45"W x 30"H x variable length	45"W x 30"H x variable length	42"W x 42"H x variable length
Bale Tier	4 wire tie automatic	4 wire tie automatic	6 wire tie automatic
Feed Opening	45"W x 60"L nominal	45"W x 60"L nominal	42"W x 64"L nominal
Operating Pressure	2,600 psi.	2,700 psi.	2,700 psi.
Platen Force	100,000 lbs.	135,000 lbs.	212,000 lbs.
Cylinder	7"	8"	10"
No-load Cycle	15 second*	10 second*	15 second*
Motor	30hp T.E.F.C 3/60/460VAC	60hp T.E.F.C 3/60/460VAC	Twin 40hp T.E.F.C. 3/60/460VAC
Shipping Weight:	23,000 lbs.**	27,000 lbs.**	33,000 lbs.**

72 Series

Consult Maren factory for detailed machine specifications and drawings. Specifications subject to change without notice.

Standard Features Include: Built to ANSI & OSHA standards - NEMA 12 dust tight electrical cabinet -Color touch screen panel - Regenerative hydraulic circuit - Ny-Oil ram shoes - Allen-Bradley PLC, Automatic photo cycle control - Low oil / Hot oil shutdown - Bale run out slide.

Options: Custom bale sizes, over size feed hoppers, rotary pre-compression door, slick stock tension system, high speed power packs, oil cooler packages, automatic water mister, high level watchman eyes and wire coil loading systems.







Sold and Serviced by:

MAREN ENGINEERING CORPORATION P.O. Box 278 South Holland, IL 60473 USA

720E-S-X-40R

Telephone: 708.333.6250 Toll Free: 800.875.1038 Fax: 708.333.7639 sales@marenengineering.com

IN CANADA

**Telephone: 905.632.0562** Toll Free: 800.678.9516

For more information visit, www.marenengineering.com