MODEL PR-480/120 TURNING ROLL

The Model PR-480/120 Turning Roll has a capacity of 240 tons turning and 60 tons support. It features Pandjiris' exclusive torque-tube wheel design sealed bearings, alloy shafts. The power roll uses an AC Motor coupled to a mechanical Vari-Drive to provide speed adjustment through out the speed range identified below. A hand pendant is provided with "Forward-Stop-Reverse" buttons. Speed adjustment is made with the hand crank in the vari-drive. This product is wired for 230/460 volts, 3 phase, 60 cycle, draws 16 amps @ 230 VAC. All wiring conforms to National Electrical Code Standards.

Turning Capacity 480,000 lbs.
Tractive Effort 22,171 lbs
Load Capacity 120,000 lbs.
Pipe Diameter Range 12" thru 21'
Speed Range 4.5 to 39 ipm

Motor Horse Power Rating 5 HP AC Motor (Vari-Drive)


Wheel Diameter 20" Combined Wheel Face 25"

The Model IR-120 Idler Roll has 60 tons support capacity.

Weight Capacity of IR-120	J00 lbs
Weight Capacity of (1) PR-480 with (1) IR-120	ງ00 lbs
Weight Capacity of (1) PR-480 with (2) IR-120	ງ00 lbs
Weight Capacity of (1) PR-480 with (3) IR-120	000 lbs

Α	Axle Height	20"
В	Wheel Height	30-1/8"
С	Wheel Diameter	20"
D	Spacing for Cylinder ø 36" - 108"	43"
Е	Spacing for Cylinder ∅ 60" - 153"	59-1/2"
F	Spacing for Cylinder ø 102" - 202"	76"
G	Spacing for Cylinder	92-1/2"

Н	Overall Length Power Roll	170-1/2"
Ι	Overall Width Power Roll	55-1/2"
Н	Frame Width Power Roll	36"
K	Combined Wheel Face	25"
L	Overall Length Idler Roll	125-1/4"
М	Axle Height	20-1/8"
N	Wheel Height	30-1/8"
0	Frame Width Idler Roll	36"



Terms: Pandjiris, Inc. standard terms and conditions apply, f.o.b. Factory, St. Louis, Missouri, or designated ship point.

Delivery: Consult Factory Approximate shipping weight: PR-480 7,100 lbs. IR-120 3,950 lbs.

PRICE LIST

For Bulletin No. : N/A Effective Date : July 1, 2000

Page Number : C-31

PANDJIRIS, INC

5151 Northrup • St. Louis, MO 63110 • (314) 776-6893

PR SERIES TURNING ROLLS Optional Accessories

For electric remote speed control pendant on 25' of cable in place of Vari-Drive hand crank speed adjustment

For special voltages, PR-400/200 thru PR-480/120

PRICE LIST

For Bulletin No. :

Effective Date : June 1, 1995

Page Number : C-32