

2013/2415 Bandsaw



The Gold Standard Since 1921.®

POWERMATIC®

2013/2415 Bandsaw

FEATURES

Powerful totally enclosed fan cooled motor to keep out dust for longer life and maximum performance

Extra large cast iron table offers more work area in front of the blade

Table tilts 45° to the right and 10° to the left and comes standard with a T-slot miter gauge

Cast iron drive wheels are balanced and equipped with vulcanized rubber tires for positive blade tracking

Lower wheel brush eliminates sawdust buildup

Convenient foot brake for rapid stops

Fully adjustable blade guard

4" dust collection port for connection to workshop dust collection system

Two speed drive pulley

Extra wide flange and heavy-duty trunnion assembly provides extra durability while eliminating any flexing of the table



New Crank handle tilts Table 45° right and 10° left

Model Number	2013	2415
Stock Number (2HP, 1Ph, 230V)	1791257	na
Stock Number (3HP, 1Ph, 230V)	na	1791259
Stock Number (3HP, 3Ph, 230/460V*)	1791258	na
Stock Number (5HP, 3Ph, 230/460V*)	na	1791260
Blade Speeds (SFPM)	2000 and 4000	2000 and 4000
Thickness Capacity, Maximum (in.)	12-3/8	14-3/8
Width Capacity, Maximum (in.)	20	24
Table Size (in.)	24x24	24x28
Table Tilt (deg.)	45 right, 10 left	45 right, 10 left
Approximate Blade Length (in.)	158-1/2	180-1/2
Blade Widths (in.)	1/4 minimum, 1-1/2 maximum	1/4 minimum, 1-1/2 maximum
Switch	magnetic	magnetic
Dust Collection Minimum CFM Required	600	600
Table Height at 90° (in.)	35-1/4	35-3/8
Floor Space Required (in.)	39x45-1/2	39x51-1/2
Shipping Weight (lbs.)	970	1190

*Pre-Wired 230Volt