

	WELD WIRE 160 TON TURNING ROLL
<i>SPECIFICATIONS</i>	<i>Size 160</i>
<i>Drive Roll</i>	WWRD-160
<i>Idler Roll</i>	WWRI-160
<i>Load Capacity (per unit)</i>	80 ton/160,000lbs.
<i>Load Capacity (1 drive & 1 idler)</i>	160 ton/320,000lbs.
<i>Load Capacity (1 drive & 2 idlers)</i>	240 ton/480,000lbs.
<i>Diameter Range</i>	8" – 18'
<i>Wheels</i>	(3) 20" diameter w/24" face, polyurethane
<i>Motor</i>	5 hp AC
<i>Speed</i>	1.2-38IPM
<i>Gearbox</i>	Primary gearbox w/secondary gearboxes
<i>Electrical Power</i>	440volt/60hz standard
<i>Control</i>	Variable speed programmable AC
<i>Hand Pendant</i>	Speed control, rapid, for/rev, start, stop w/25' cable
<i>Dimensions (drive)</i>	132"L X 52"W X 28"H
<i>Dimensions (idler)</i>	115"L X 48"W X 28"H
<i>Shipping Weight (drive)</i>	4,400 lbs.
<i>Shipping Weight (idler)</i>	3,500 lbs.
<i>Options:</i>	
<i>Foot Control</i>	Variable speed or On/Off
<i>Wheels</i>	Steel