58BD & 58BW Portable/Convertible Manual Bandsaw





Model 58BD & 58BW Bandsaws

ations

Standard Features

Rigid Welded Steel Frame & Bed

Convertible (Horizontal/Vertical)

Mobile - Includes Retractable Wheels and Pull Handle

Hydraulic Feed Control with Adjustable Counterbalance Spring

Work Table for Vertical Operation

Adjustable Stock Stop

Ball Bearing Blade Guides

Baldor® Blade Motor

Three Band Speeds

Blade Brush

Safety Switch and Overload Protection

Quick Acting Vise

Precision Ground Bed

Replaceable Pivot Bar and Bushings

Auto Shut-Off at End of Cut

OSHA Blade Guards

Tiger Tooth® Blade

Available Factory Installed Options

3/4" Blade (Capacity Limited to 7" x 11" with This Option)

3/4hp Motor

Stock Stand

Spare Blade Package

Specifications

Capacity
Round 9-1/2"
Flat 11"
Rectangular 9-1/2" x 11"
45° Angle 5-1/2" x 5-1/2"

Vertical Capacity
Throat Depth 6-1/4"
Throat Height 9-1/2"
Work Table 8" x 10"

Blade Size 1/2" x .025 x 7'9" (93")
Blade Speeds 76-141-268 SFPM

Blade Guides Six Sealed Ball Bearings on

Cast Iron Supports

Blade Motor 1/2hp Single Phase ODP

Vise Control Manual Screw/Quick Action

Swivel Vise To 45°

Band Wheels 11" Cast Iron
Bed Height 26"

Floor Area 26"W x 54"L

Shipping Weights

58BD 350 Lbs. 58BW 385 Lbs.

The Wellsaw Model 58B is available in Wet (flood coolant) or Dry sawing configurations. This rugged model provides large capacity yet is highly portable. Our most versatile machine, it quickly converts from horizontal to vertical operation.

