

Totally Reliable Parts Cleaning

- Low competitive cost—quick and easy to install
- Spray washing with optional dunk
- Simple to operate and maintain
- 100% performance-proven

BeaverMatic washers are batch-type, power spray units that provide totally dependable cleansing action. They feature a high-capacity centrifugal

pump which supplies washing solution to the spray nozzles and ejects it at 60 psi. BeaverMatic's strategically engineered spray pattern penetrates the load, removing all deposits and surface contaminants.


Combining the advantages of low cost, quick installation and simplified maintenance, these wash units are compatible for use with all standard furnace equipment. As a key component of the BeaverMatic line, they have demonstrated their reliability in heat treat plants throughout the USA.


Features

- Washing solution heated to average of 180°F., gas or electric
- Disc-type oil skimmer for discharge to collection barrel
- In-line pump/strainer
- Water level float valve
- Pneumatically operated front door
- Complete coverage by 27 spray nozzles at 60 psi on sides, top and bottom
 - Operating timer
 - Furnished with all necessary electrical/mechanical drawings and a comprehensive operator's manual
 - Meets current EPA and OSHA standards



BEAVERMATIC





New 24"W x 36"D x 20"H multi-zone BeaverMatic unit combines temper furnace processing with a two chamber washer in one continous operation.

SPRAY WASHER SIZES/SPECIFICATIONS

Working Dimensions						Overall Dimensions		
Width	Lengtl	n Height	Load Lbs.	Pump H.P.	Tank Capacity Gallons	Width	Length	Height
18"	24"	14"	350	3	350	4'-6"	8'-8"	7'- 4"
18"	24"	20"	400	3	400	4'-6"	8'-8"	7'-10"
24"	36"	20"	500	3	400	4'-8"	9'-8"	7'-10"
24"	36"	26"	750	3	400	4'-8"	9'-8"	8'-7"
30"	48"	20"	1,000	5	550	5'-2"	11'-8"	7'-10"
30"	48"	26"	1,500	5	550	5'-2"	11'-8"	8'-7"
30"	48"	32"	2,000	7 1/2	550	5'-2"	11'-8"	9'-3"
36"	48"	20"	1,500	5	600	5'-8"	11'-8"	7'-10"
36"	48"	26"	2,000	7 1/2	600	5'-8"	11'-8"	8'-7"
36"	48"	32"	2,000	7 1/2	600	5'-8"	11'-8"	9'-3"
48"	48"	32"	3,000	10	600	6'-8"	11'-8"	9'-3"
48"	48"	38"	4,000	10	600	6'-8"	11'-8"	10'-0"
48"	72"	36"	4,000	20	1,000	6'-8"	12'-8"	10'-0"
48"	72"	48"	5,000	25	1,250	6'-8"	12'-8"	11'-0"







Phone: 815.963.0005 Fax: 815.963.5673 www.beavermatic.com