

Dial Reading Viscometer

the original that became the world standard

The Worldwide Standard

Viscometer

Easy-to-Select Speeds

Electronic Drive

means quiet,
reliable operation

Analog display

- Shows % Torque
- Use Factor Finder
to convert reading
to centipoise

Simple-to-use,

easy setup

2-Year Limited Warranty

Available in explosion proof

U.L. Class 1, Division 1,
Group D locations
(w/o Electronic Drive)

Accuracy: $\pm 1.0\%$ of range

Repeatability: $\pm 0.2\%$



*Easy Speed
Adjustment and On/
Off Control*

What's Included?

Instrument
6 spindles (RV/HA/HB)
or 4 spindles (LV)
Spindle Guard Leg*
Lab Stand (Model A)
Carrying Case
*Not applicable to HA or HB torque models

Optional Accessories

Viscosity Standards
RV/HA/HB-1 Spindle
Quick Action Lab Stand
Temperature Bath
Small Sample Adapter
UL Adapter
Thermosel
Spiral Adapter
DIN Adapter
Quick Connect/Extension Links
Vane Spindles)

MODEL	VISCOSITY RANGE cP(mPa•s)		SPEEDS	
	Min.	Max.	RPM	Number of Increments
LVT	1†	2M	.3-60	8
RVT	100††	8M	.5-100	10
HAT	200††	16M	.5-100	10
HBT	800††	64M	.5-100	10

† 1 cP achieved with UL Adapter accessory. 15 cP on LV with standard spindles.
†† Minimum viscosity is achieved with optional RV/HA/HB-1 spindle.
M = 1 million cP = Centipoise mPa•s = Millipascal•seconds

ISO 9001:2008 CERTIFIED

