


Open Rotary Screw Compressors



Compressed Air Systems

Simplicity. It's What We Do.

www.compressed-air-systems.com

1-800-531-9656 Fax 972-352-6364



Rotary Screw 5-125 HP

RS Series Screw Compressors

The CAS 5-125 HP screw compressors are a great fit for almost any application. The units have a 100% duty cycle so you cannot overwork the compressor. The simple maintenance and once a year oil change has made this series a perfect fit for dry cleaners, body shops, cabinet shops and many other applications.

- Operating pressures from 100-180 psi
- Low tip speeds on air end for long life
- Less than 3 ppm oil carry over
- One solenoid valve to operate machine
- Quiet operation
- Spin on separator and oil filter
- Available with receiver
- Oil after-cooler standard on all models
- 8000 hour full synthetic oil standard
- Order 125, 150, 175 or 195 operating pressure at no extra charge
- Analog controls. No unnecessary and unreliable microprocessor
- 5-year extended warranty available for air end
- Heavy-duty air filter
- German airend components

Options Available:

- Soft starter
- Microprocessor
- TEFC motor
- Variable speed drive
- Explosion proof motor

Elite Features:

- Air/ oil cooler
- Timed shut down
- Auto tank drain
- Rubber mounting pads



**FREIGHT
PREPAID**

Rotary Screw 5-250 HP

RS Series Screw Compressors

5-10HP RS SERIES SCREW COMPRESSORS								
Model	HP	CFM @150psi	CFM @ 125psi	Tank Size	Vert/Horz	Voltage	Phase	Amps @ 230 Volt
RS53V80	5	16	19	80	V	208-230-460	3	16
RS53H80	5	16	19	80	H	208-230-460	3	16
RS51V80	5	16	19	80	V	208-230	1	24
RS51H80	5	16	19	80	H	208-230	1	24
RS73V80	7.5	26	29	80	V	208-230-460	3	18
RS73H80	7.5	26	29	80	H	208-230-460	3	18
RS71V80	7.5	26	29	80	V	208-230	1	32
RS71H80	7.5	26	29	80	H	208-230	1	32
RS103V80	10	38	40	80	V	208-230-460	3	28
RS103H80	10	38	40	80	H	208-230-460	3	28
RS103V120	10	38	40	120	V	208-230-460	3	28
RS103H120	10	38	40	120	H	208-230-460	3	28
RS101V80	10	35	37	80	V	208-230	1	54
RS101H80	10	35	37	80	H	208-230	1	54
RS101V120	10	35	37	120	V	208-230	1	54
RS101H120	10	35	37	120	H	208-230	1	54
RS153V8031	15	59	57	80	V	208-230-460	N	42
RS153H120	15	55	68	120	H	208-230-460	N	42
RS203H120	20	78	88	120	H	208-230-460	N	54
RS253H120	25	102	108	120	H	208-230-460	N	63
RS303H120	30	125	130	120	H	208-230-460	N	72
RS403H120	40	155	160	120	H	460-480	Y	92
RS503H120	50	185	215	120	H	460-480	Y	125
RS603H120	60	225	245	120	H	460-480	Y	144
RS753H120	75	285	315	120	H	460-480	Y	172
75-250HP BASEMOUNT RS SERIES SCREW COMPRESSOR								
Model	HP	CFM @150psi	CFM @ 125psi	Tank Size	Vert/Horz	Voltage	208-230 Adder	Amps @ 230 Volt
RS75BM	75	295	335	Basemount	N/A	460-480	Y	172
RS100BM	100	400	450	Basemount	N/A	460-480	Y	238
RS125	125	475	500	Basemount	N/A	460-480	Y	N/A
All above units available base mounted without receiver								





Compressed Air Systems, LLC

2626 Skyway Drive
Grand Prairie, TX, 75052

1-800-531-9656

Fax 972-352-6364

Simplicity. It's What We Do.