



SAN SHING MACHINERY

三 興 機 器 工 業



SE-32120



三興 重切削精密車床

HEAVY DUTY PRECISION LATHE

SERIES SE-28 SE-32 SE-36

重切削精密車床 規格表

HEAVY DUTY PRECISION LATHE SPECIFICATION

項 目 ITEM		SE-28				SE-32				SE-36			
機 種 MODEL		SE-2840 SE-2860 SE-2880 SE-28100		SE-28120 SE-28160 SE-28200 SE-28240 SE-28280		SE-3240 SE-3260 SE-3280 SE-32100		SE-32120 SE-32160 SE-32200 SE-32240 SE-32280		SE-3640 SE-3660 SE-3680 SE-36100		SE-36120 SE-36160 SE-36200 SE-36240 SE-36280	
工作範圍 CAPACITY													
床面上最大旋徑 Swing Over Bed		730mm (28")				830mm (32")				930mm (36")			
橫送台上最大旋徑 Swing Over Cross Slide		500mm (19.5")				600mm (23.5")				700mm (27.5")			
凹口上最大旋徑 Swing in Gap		1020mm (40")				1120mm (44")				1220mm (48")			
凹口工作物長度 Width of Gap		304mm (12")											
兩心間距離 Distance Between Centers		1000mm (40") ~ 7000mm (280")											
主軸箱 HEADSTOCK													
主軸孔端 Spindle Bore		80mm (3 ¹ / ₈ ") , *105mm (OPT) , *153mm (OPT)				105mm (4 ¹ / ₈ ") , *153mm (OPT)							
主軸鼻端 Spindle Nose		A2-8, *A2-11, *D1-8, *D1-11 (OPT)											
中心針斜度 (莫氏) Taper of Center		M. T. NO. 5											
主軸變速範圍 Range of Spindle Speeds		15-1000, *10-700RPM (OPT)											
主軸變換段數 Number of Spindle Speeds		12Changes											
進給與車牙 FEEDS & THREADS CUTTING													
縱向進刀量範圍 Longitudinal Feeds		0.05-0.7mm/rev											
橫向進刀量範圍 Cross Feeds		0.025-0.35mm/rev											
英制螺紋 (徑節螺紋) Inch Threads		2-28Thread/in, (D. P. 4-56)											
公制螺紋 (模數螺紋) Metric Threads		0.8-14mm/Thread, (M. P. 0.5-7)											
導螺桿直徑及螺距 Leadscrew		45mm (1 3/4") × 2T.P.I. or P12mm (OPT)											
滑 座 CARRIAGE													
橫送台移動範圍 Cross Slide Travel		425mm 16-1/2"											
複式刀座移動範圍 Compound Rest Travel		250mm 10"											
尾 座 TAILSTOCK													
心軸直徑 Quill Diameter		80mm 3-1/8", 95mm (OPT)											
心軸行程 Quill Travel		230mm 9"											
頂心斜度 Taper of Quill Center		M. T. NO. 5											
床 體 BED													
床面寬度 Width of Bed		460mm (18 ¹ / ₈ ")											
主馬達 Main Motor		10HP, 15HP, 20HP (OPT)											
床身長度 Length of Bed 單位 CM		長/L	40	60	80	100	120	160	200	240	280		
		SE	243	293	343	393	443	543	643	743	843		
裝箱尺寸 (約) Packing Size 單位 CM (L × W × H)		SE	295	345	395	445	500	600	700	800	900		
													寬 W 130 高 H 180
重 量 (約) Weight (Approx) 單位 KG (淨重/NW)		SE	3000	3300	3600	4000	4300	4900	5500	6100	6700		

標準附件

STANDARD

- 連結板 1個
- 心軸套筒 1個
- 中心針 2支
- 刀架螺絲把手 1個
- 地腳螺栓 1個
- 工具箱 1個
- 三爪夾頭 12" 1個
- 中心架 1個
- Back Plate 1PC
- Center Sleeve 1PC
- Center (M.T.5#) 2PCS
- Tool Post Wrench 1PC
- Anchor Bolt 1SET
- Tool Box & Tool 1SET
- 3-Jaw Scroll Chuck 12" 1PC
- Steady Rest 1PC

特別附件

OPTION ACCESSORIES

- 四爪夾頭 18" 1個
- 面盤 30" 1個
- 斜度裝置 1組
- 跟刀架 1個
- 冷卻泵浦 1組
- 縱向快速移動裝置 1組
- 4-Jaw Independent Chuck 18" 1PC
- Face Plate 30" 1PC
- Taper Turning Attachment 1SET
- Follow Rest 1PC
- Coolant Pump 1SET
- Longitudinal Rapid Traverse Device 1SET

三興機器工業股份有限公司
SAN SHING MACHINERY IND. CO. LTD.
40245台中市南區復興路二段71巷77弄3號
3, Alley 77, Lane 71, Sec. 2, Fu-Shing Road,
Taichung, 40245 Taiwan.
TEL: 886-4-2262-3161~3 FAX: 886-4-2262-4648
E-mail: ssmcom@ms41.hinet.net san.shing@hotmail.com
http://www.sanshinglathe.com

經銷商
AGENT

2015.01.01

* Specifications are subject to change without notice for further design improvement. * 本公司擁有設計變更及規格變更的權力，若有變更恕不另行通知。